

JMAWD-26XP Product Details



JMAWD-26XP  
(1617126-6)

TE Internal Number: 1617126-6

Active

Military/Aerospace High Performance Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- MAD TO-5 Relay Series
- Input Voltage = 26.5 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 1 A
- Non Polarized, Monostable Coil Magnetic System

View all Features

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"><li>• <a href="#">RELAY</a> (PDF, English)</li></ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"><li>• None Available</li></ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Product Line Information</a></li></ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Tooling</a></li></ul>
<a href="#">List all Documents</a>	

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"><li>• Termination Type = Long Leads</li></ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"><li>• Input Voltage (VDC) = 26.5</li><li>• Contact Current Rating (A) = 1</li><li>• Coil Polarity Protection Diode = Without</li><li>• Transistor Driver = Without</li><li>• Coil Resistance (Ω) = 1560</li><li>• MOSFET Driver = Without</li><li>• Coil Power Measurement = Milliwatts</li><li>• Coil Power, Nominal (mW) = 450</li><li>• Actuating System = DC</li><li>• Shock = 75 G's, 6ms</li><li>• Vibration = 30G's, 10 to 3000Hz</li></ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Series</a> = MAD TO-5 Relay</li></ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"><li>• Mounting Options = PC Board</li><li>• Enclosure Type = Hermetically Sealed</li><li>• Approved Standards = M39016 Qualified, P Level</li></ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"><li>• <a href="#">Contact Arrangement</a> = 2 Form C, DPDT, 2 C/O</li><li>• Coil Magnetic System = Non Polarized, Monostable</li><li>• Coil Suppression Diode = With</li></ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"><li>• Government/Industry Qualification = Yes</li><li>• Government/Industry Part Number = M39016/15-033P</li><li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li><li>• <a href="#">Lead Free Solder Processes</a> = Not suitable for lead free processing</li></ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"><li>• Temperature Range (°C) = -65 - +125</li></ul> <p><b>Other:</b></p> <ul style="list-style-type: none"><li>• Brand = CII</li></ul>

BOOKMARK