

Mechanical Attachment	
Mounting Options	PC Board
Electrical Characteristics	
Input Voltage (VDC)	5
Contact - Rated Current (A)	1
Coil Suppression Diode	With
Coil Polarity Protection Diode	Without
Coil - Resistance (Ω)	50
Coil Power Measurement	Milliwatts
Coil - Rated Power, DC (mW)	500
Actuating System	DC
Shock	75 G's, 6ms
Vibration	30G's, 10 to 3000Hz
Termination Features	
Termination Type	Long Leads

Configuration Features	
Contact - Arrangement 	2 Form
Coil - Magnetic System	Non Po
Transistor Driver	Withou
Industry Standards	
Government/Industry Qualification	Yes
Government/Industry Part Number	M3901
RoHS/ELV Compliance 	Not EL
Lead Free Solder Processes 	Not su proces
Approved Standards	M3901
Conditions for Usage	
Temperature Range ($^{\circ}\text{C}$)	-65 -
Other	
Series 	MAD T
Brand	CII

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[Global Accessibility Statement](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)