

Not EU RoHS or ELV Compliant

- MST TO-5 Relay Series
- Input Voltage = 18 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 1 A
- Non Polarized, Monostable Coil Magnetic System

[View all Features](#)

TE Internal Number: 1617170-3

Active

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

- None Available

- [RELAY](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- Tooling

List all Documents

- Termination Type = Long Leads

- Input Voltage (VDC) = 18
- Contact Current Rating (A) = 1
- Coil Polarity Protection Diode = Without
- Transistor Driver = With
- Coil Resistance (Ω) = 1600
- MOSFET Driver = Without
- Coil Power Measurement = Milliwatts
- Coil Power, Nominal (mW) = 203
- Actuating System = DC
- Shock = 75 G's, 6ms
- Vibration = 30G's, 10 to 3000Hz

- **Series** = MST TO-5 Relay

- Mounting Options = PC Board
- Enclosure Type = Hermetically Sealed
- Approved Standards = M28776 Qualified, P Level

- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Coil Magnetic System = Non Polarized, Monostable
- Coil Suppression Diode = With

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M28776/3-021P
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Not suitable for lead free processing

- Temperature Range (°C) = -65 - +125

- Brand = CII

BOOKMARK

Careers

[Site Map](#)[Manage Your Account](#)

Enter your email address

Follow us on: