This browser does not have Java enabled.

TE connectivity

My Cart | My Part Lists | Sign In/Register | English (Change)

Have a Question? Chat with a Product Information Specialist

What can we help you find?

| Products | Industries | Resources | About TE | My Account | Innovation | Support Center |

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details

1734577-3 Product Details

Share | Print | Email

1734577-3

TE Internal Number: 1734577-3

✔ Active

📄 View 3D PDF

PCB Mounted Jacks - Single Port, Multi-port and Stacked

🍃 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:
- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ45

View all Features

Add to My Part List | Request Sample | Find Similar Products | Buy Product

Quick Links
▷ Pricing & Availability
▷ Search for Tooling
▷ Product Feature Selector
▷ Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- MODULAR JACK, RJ45, 8P8C, DIP TYPE. (PDF, English)

Catalog Pages/Data Sheets:
- None Available

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files: (CAD Format & Compression Information)
- 2D Drawing (DXF, Version C)
- 3D Model (IGES, Version C)
- 3D Model (STEP, Version C)

Additional Information:
- Product Line Information

Related Products:
- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Top Entry (Vertical)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 3
- LED = With
- Grounding Options = PCB Ground
- Panel Stops = Without
- Keyed = No
- Profile = Standard
- Color = Black
- Shield Material = Brass

Mechanical Attachment:
- Panel Mount Retention = Without
- Flanged = No

Electrical Characteristics:
- Shielded = Yes

Termination Features:
- Solder Tail Contact Plating = Gold Flash over Nickel

Dimensions:
- Height (mm [in]) = 16.50 [0.650]
- PCB Tail Length (mm [in]) = 3.25 [0.1281]
- PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]

Body Features:
- Inverted Jack Face = No
- Shield Plating = Nickel
- LED Lightpipe Material = Epoxy Resin
- PCB Ground Tab Location (mm [in]) = 3.85 [0.152]

Contact Features:
- Contact Plating, Mating Area, Material = Gold (30)
- Contact Base Material = Phosphor Bronze

Housing Features:
- Housing Material = High Temperature Thermoplastic
- UL Flammability Rating = UL 94V-0

Configuration Features:
- Preloaded = Yes
- Port Configuration = Single
- Jack Configuration = 1 x 1
- Number of Positions = 8
- Number of Contacts Loaded = 8
- Number of PCB Ground Tabs = 2

Industry Standards:
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:
- LED Position 1 Color = Green
- LED Position 2 Color = Yellow
- LED Position 3 Color = None

Packaging Features:
- Packaging Method = Tray
- Packaging Quantity = 100/Tray

Product Availability:
- Region = Asia, North America

Other:
- Brand = TE Connectivity

Corporate Information
About TE
Investors
News Room
Supplier Portal
Careers
Terms & Conditions
Privacy Policy

Quick Links
Distributor Inventory
Product Cross Reference
Documents & Drawings
Product Compliance Support Center
Site Map

Customer Support
Email or Chat With Us
Find a Phone Number
Knowledge Base
Manage Your Account

Keep Me Informed