Products

Documentation

Resources

My Account

Customer Support

Home > Products > Socket/Card Products > Product Feature Selector > Product Details

390262-5 Product Details


Have a Question? Information Specialist

Quick Links

Check Pricing & Availability Search for Tooling

Product Feature Selector

Contact Us About This Product



DIP Sockets

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)


Product Highlights:

- Socket Style = Standard
- Through Hole Contact Termination Type
- 2.54 mm Centerline
- Row-to-Row Spacing = 15.24 mm
- 40 Positions


View all Features

TE Internal Number: 390262-5 Superseded

Search for Replacement Parts







Documentation & Additional Information

Product Drawings:

DIP SOCKET, .600 CENTER LINE LADDER STYLE (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Socket Style = Standard
- Profile = Standard
- <u>Frame Style</u> = Ladder
- <u>Leq Style</u> = Straight
- PCB Mount Angle = Horizontal

- Electrical Characteristics: Insulation Resistance (MΩ) = 10,000
 - Contact Resistance (mΩ) = 30

Termination Related Features:

- Termination Post Length (mm [in]) = 3.00 [0.118]
- Solder Tail Contact Plating = Tin-Lead

Body Related Features:

- Centerline (mm [in]) = 2.54 [0.100]
- Row-to-Row Spacing (mm [in]) = 15.24 [0.600]
- Number of Positions = 40
- Mount Style = Vertical

Contact Related Features:

<u>List all Documents</u>

- Contact Termination Type = Through Hole
- Contact Base Material = Phosphor Bronze
- Contact Plating, Mating Area, Material = Tin-Lead
- Contact Style = Stamped + Formed
- Mating Contact Type = Dual Leaf

Configuration Related Features:

Height Above PC Board (mm [in]) = 5.10 [0.200]

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:

Temperature Range (°C) = -40 - +105

Packaging Related Features:

Packaging Method = Tube

Other:

Brand = AMP



Corporate Information

Who We Are

Investors

News Room

Supplier Portal Careers

Quick Links

Check Distributor Inventory

Cross Reference

Find Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat with Us

Find a Phone Number

Search Knowledge Base

Manage Your Account

Sign up for our eNewsletter

Enter your email address



Provide Website Feedback

Follow Us On:





