

Mechanical Attachment	
Mounting Options	PC Board
Electrical Characteristics	
Input Voltage (VDC)	5
Contact - Rated Current (A)	1
Coil Suppression Diode	With
Coil Polarity Protection Diode	Without
Coil - Resistance (Ω)	100
Coil Power Measurement	Milliwatts
Coil - Rated Power, DC (mW)	250
Actuating System	DC
Shock	75 G's, 6ms
Vibration	30G's, 10 to 3000Hz
Termination Features	
Termination Type	Long Leads
Body Features	
Enclosure Type	Hermetically Sealed

Configuration Features	
Contact - Arrangement 	2 Form
Coil - Magnetic System	Non Po
Transistor Driver	With
Industry Standards	
Government/Industry Qualification	Yes
Government/Industry Part Number	M2877
RoHS/ELV Compliance 	Not EL
Lead Free Solder Processes 	Not su proces
Approved Standards	M3901
Conditions for Usage	
Temperature Range (°C)	-65 -
Other	
Series 	MGST
Brand	CII

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[Global Accessibility Statement](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)