



+ RELAYS, CONTACTORS & SWITCHES  
DIP & SIP SWITCHES



✓ Active

TE CONNECTIVITY (TE)  
1P. DIP SWITCH WITH ACTION PIN POSTS

Alcoswitch | SBP , Standard

5338048-1  
TE Internal Number: 5338048-1

EU RoHS Compliant  
EU ELV Compliant

- Product Type Switch
- Contact Mating Area Plating Material Tin
- Housing Color Natural
- Housing Material Nylon - GF
- Auto-Insertable No

↓ PRODUCT DRAWING  
English

DOCUMENTATION

Product Drawings

Dip Switch Action Pin Version

PDF

English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

<div><div>Product Type</div><div>Switch</div></div> <div><div>Sealed</div><div>No</div></div> <div><div>Switch Type</div><div>DIP</div></div> <div><div>Actuator Style</div><div>Slide</div></div>
<div>Configuration Features</div> <div><div>Number of Switches</div><div>1</div></div> <div><div>Configuration (Pole-Throw)</div><div>Single Pole - Single Throw</div></div> <div><div>Number of Positions</div><div>1</div></div>
<div>Body Features</div> <div><div>Actuator Color</div><div>Red</div></div>
<div>Contact Features</div> <div><div>Contact Mating Area Plating Material</div><div>Tin</div></div> <div><div>Auto-Insertable</div><div>No</div></div> <div><div>Contact Base Material</div><div>Phosphor Bronze</div></div> <div><div>Contact Mating Area Plating Thickness (µm)</div><div>2.5</div></div> <div><div>Solder Tail Contact Plating</div><div>Tin</div></div>
<div>Termination Features</div> <div><div>Termination Post Length</div><div>3.2 mm [ .1259 in ]</div></div>
<div>Mechanical Attachment</div> <div><div>Mounting Type</div><div>ACTION PIN, Through Hole</div></div> <div><div>Mounting Angle</div><div>Vertical</div></div>
<div>Housing Features</div> <div><div>Housing Color</div><div>Natural</div></div> <div><div>Housing Material</div><div>Nylon - GF</div></div> <div><div>Centerline</div><div>2.54 mm [ .1 in ]</div></div>
<div>Dimensions</div> <div><div>Length</div><div>5.08 mm [ .199 in ]</div></div> <div><div>Height</div><div>8.5 mm [ .334 in ]</div></div>
<div>Usage Conditions</div> <div><div>Operating Temperature Range (°C)</div><div>-25 – 70</div></div>
<div>Industry Standards</div> <div><div>UL Flammability Rating</div><div>UL 94V-0</div></div>
<div>Packaging Features</div> <div><div>Packaging Quantity</div><div>2000</div></div> <div><div>Packaging Method</div><div>Box &amp; Carton</div></div>

Statement of Compliance

**Statement of Compliance**

PDF

---