



+ RELAYS, CONTACTORS & SWITCHES
DIP & SIP SWITCHES



✓ Active

TE CONNECTIVITY (TE)
ADF0604=DIP SWT,FLUSH,THRU/HL
[Alcoswitch](#) | [Alcoswitch DIP](#) , [Alcoswitch DIP ADF](#)

1825002-9
TE Internal Number: 1825002-9
Alias ID: ADF0604

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Product Type Switch
Contact Mating Area Plating Material Gold Flash
Housing Color Black
Housing Material Polyphenylene Sulfide (PPS)
Auto-Insertable Yes

↓ **PRODUCT DRAWING**
English

DOCUMENTATION

Product Drawings
DIP SWITCH, ADF THRU HOLE
PDF
English

Catalog Pages/Data Sheets
SWITCHES_CORE_PROGRAM_CATALOG
PDF
English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Product Type** Switch
- Sealed** No
- Switch Type** DIP
- Actuator Style** Flush, Slide

Configuration Features

- Number of Switches** 6
- Configuration (Pole-Throw)** Single Pole - Single Throw
- Number of Positions** 6

Electrical Characteristics

- Voltage Rating (VDC)** 5

Body Features

- Actuator Color** White

Contact Features

- Contact Mating Area Plating Material** Gold Flash
- Auto-Insertable** Yes
- Contact Current Rating (A)** 1
- Contact Base Material** Copper Alloy
- Contact Mating Area Plating Thickness (µin)** 1.2
- Solder Tail Contact Plating** Gold over Nickel

Termination Features

- Termination Post Length** 4 mm [.157 in]

Mechanical Attachment

- Mounting Type** Through Hole
- Mounting Angle** Vertical

Housing Features

- Housing Color** Black
- Housing Material** Polyphenylene Sulfide (PPS)
- Centerline** 2.54 mm [.1 in]

Dimensions

- Length** 17.22 mm [.677 in]
- Height** 4 mm [.138 in]

Usage Conditions

- Operating Temperature Range (°C)** -30 – 85

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Quantity 25

Packaging Method Tube

PRODUCT COMPLIANCE +

Statement of Compliance

Statement of Compliance

PDF