

+ RELAYS, CONTACTORS & SWITCHES

DIP & SIP SWITCHES



✓ Active

TE CONNECTIVITY (TE)

ADP08STR04=PIANO DIP SWITCH

Alcoswitch | Alcoswitch DIP , Alcoswitch DIP ADP & ADPA

2-1571999-9

TE Internal Number: 2-1571999-9

Alias ID: ADP08STR04

EU RoHS Compliant EU ELV Compliant

Product Type Switch

Contact Mating Area Plating Material Gold

Housing Color Black

Housing Material Polyphenylene Sulfide (PPS)

Auto-Insertable Yes



PRODUCT DRAWING

± English



★ 3D PDF

DOCUMENTATION

Product Drawings

DIP SWITCH ASSEMBLY ADP/PA SERIES

PDF

English

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

English Customer View Model 3D_STP.ZIP **English** Catalog Pages/Data Sheets SWITCHES_CORE_PROGRAM_CATALOG PDF **English** Product Environmental Compliance TE Material Declaration MD_2-1571999-9_04092014725_dmtec PDF **English FEATURES** Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity. Product Type Features **Product Type** Switch Sealed No **Switch Type** DIP Actuator Style Piano (Side Actuated) Configuration Features Number of Switches 8 Configuration (Pole-Throw) Single Pole - Single Throw **Number of Positions** 8 **Electrical Characteristics Voltage Rating (VDC)** 5 **Body Features Actuator Color** White **Contact Features Contact Mating Area Plating Material** Gold Auto-Insertable Yes Contact Current Rating (A) 1 **Contact Base Material** Copper Alloy Contact Mating Area Plating Thickness (µin) 1.2 **Solder Tail Contact Plating** Gold over Nickel

Customer View Model

3D_IGS.ZIP

Downloaded from Arrow.com.

Termination Features Termination Post Length 4 mm [.157 in] **Termination Style** Outside L Mechanical Attachment **Mounting Type** Surface Mount Mounting Angle Vertical **Housing Features Housing Color** Black Housing Material Polyphenylene Sulfide (PPS) Centerline 2.54 mm [.1 in] On Position Lever Down **Dimensions Length** 22.3 mm [.878 in] Height 6 mm [.236 in] **Usage Conditions Operating Temperature Range (°C)** -30 – 85 **Industry Standards UL Flammability Rating** UL 94V-0 **Packaging Features** Packaging Quantity 500 Packaging Method Tape & Reel **PRODUCT COMPLIANCE** Statement of Compliance **Statement of Compliance** PDF