



+ RELAYS, CONTACTORS & SWITCHES

SOLID STATE POWER RELAYS



✓ Active

TE CONNECTIVITY (TE)
JDS9-1Y = M28750/9-001Y
CII

JDS9-1Y
TE Internal Number: 1-1617069-1
Mil-Spec: M28750/9-001Y

[Not EU RoHS or ELV Compliant](#)
[Find Compliant Alternatives](#)

Output Voltage Rating (AC Relays) **250 Vrms**

Relay Type **High Performance Solid State**

Input Voltage (VDC) **3.8 – 32**

Operating Temperature Range (°C) **-55 – 110**

Mounting Type **PC Board**

Catalog Pages/Data Sheets

[RELAY](#)
[PDF](#)
[English](#)

Please review product documents or [contact us](#) for the latest agency approval information.




Product Type Features	Relay Type	High Performance Solid State
	Enclosure Type	Sealed
	Product Type	Relay
	Screening Level	Y
Electrical Characteristics	Output Voltage Rating (AC Relays)	250 Vrms
	Input Voltage (VDC)	3.8 – 32
	Vibration	20G's, 10 – 2000Hz
	Insulation Initial Dielectric Between Contacts and Coil (Vrms)	1500
	Output Current Rating (A)	2
	Shock	1500G's, .5ms
Body Features	Packaging Style	DIP

Termination Features	Termination Type	Through Hole
Mechanical Attachment	Mounting Type	PC Board
Usage Conditions	Operating Temperature Range (°C)	-55 – 110
Other	Additional Features	None
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

BOARD-TO-BOARD HEADERS & RECEPTACLES



34 MODII HORZ DR CE
535512-4

Save to List

Find Similar Products

SPLICES



D-436-0096
650136-000

Save to List

Find Similar Products

MULTICORE CABLE



44A1121-22-0/9-9
44A1121-22-0/9-9-MX

Save to List

Find Similar Products

HEAT SHRINK TUBING



RW-200-1-0-SP
RW-200-1-0-SP

Save to List

Find Similar Products

>