





Mechanical Attachment		Configuration Features	
Mounting Options	PC Board	Contact - Arrangement 	2 Form
Electrical Characteristics		Coil - Magnetic System	Non Po
Input Voltage (VDC)	26.5	Transistor Driver	Without
Contact - Rated Current (A)	1	Industry Standards	
Coil Suppression Diode	With	Government/Industry Qualification	Yes
Coil Polarity Protection Diode	Without	Government/Industry Part Number	M3901
Coil - Resistance (Ω)	3200	RoHS/ELV Compliance 	Not EL
Coil Power Measurement	Milliwatts	Lead Free Solder Processes 	Not su proces
Coil - Rated Power, DC (mW)	219	Approved Standards	M3901
Actuating System	DC	Conditions for Usage	
Shock	75 G's, 6ms	Temperature Range ($^{\circ}\text{C}$)	-65 -
Vibration	30G's, 10 to 3000Hz	Other	
Termination Features		Series 	MGSD
Termination Type	Long Leads	Brand	CII
Body Features			
Enclosure Type	Hermetically Sealed		

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[Global Accessibility Statement](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)