

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:**

- None Available

[List all Documents](#)**Product Features** (Please use the Product Drawing for all design activity)**Product Type Features:**

- Actuator Style = Extended, Side
- Series = MSS
- Mount Angle = Vertical
- Terminal Configuration = Standard
- Grade = Instrumentation
- Termination Type = PC
- PCB Mount Retention = With

**Electrical Characteristics:**

- Contact Rating = 300mA @ 125 VAC

**Dimensions:**

- Actuator Length (mm [in]) = 4.20 [0.165]

**Body Features:**

- [Number of Positions](#) = 3
- Actuator Color = Black
- Mount Style = Through-Hole
- PCB Tail Length (mm [in]) = 3.00 [0.118]
- PCB Mount Retention Type = Guide Posts
- Actuator Material = Polyester

**Contact Features:**

- Contact Plating

**Housing Features:**

- UL Flammability

**Configuration Features:**

- Configuration
- Threaded Cap
- Number of A

**Industry Standards:**

- [RoHS/ELV Compliance](#)
- [Lead Free Solder](#)  
solder cap
- RoHS/ELV Compliance

**Identification Markings:**

- Stamped Markings

**Other:**

- Brand = Alcon

**Corporate Information**[About TE](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)[Terms & Conditions](#)[Privacy Policy](#)**Quick Links**[Check Distributor Inventory](#)[Cross Reference Products](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)**Customer Support**[Email or Chat With Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage Your Account](#)