

1825163-4 Product Details

 Share  Print  Email



1825163-4
(STS250PC04)

TE Internal Number: 1825163-4

 Active

Slide Switches

 Always EU RoHS/ELV Compliant ([Statement of Compliance](#))

Product Highlights:

- 5 Positions
- Double Pole - Five Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Black
- STS Series

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [SWITCH-SLIDE \(DP*T\) P/N STS2*0PC](#) (PDF, English)

Catalog Pages/Data Sheets:

- [SWITCHES CORE PROGRAM CATALOG](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Configuration (Pole-Throw) = Double Pole - Five Throw
- Actuator Style = Top
- Series = STS
- Mount Angle = Vertical
- Terminal Configuration = Standard
- Grade = Economy
- Termination Type = PC
- PCB Mount Retention = Without

Electrical Characteristics:

- Contact Rating = 250mA @ 125 VAC

Body Features:

- [Number of Positions](#) = 5
- Actuator Color = Black
- Mount Style = Through-Hole
- Switch Style = Low Profile
- PCB Tail Length (mm [in]) = 2.79 [0.110]
- PCB Mount Retention Type = None
- Actuator Material = POM
- Actuator Travel = 2.50 [.098]

Contact Features:

- Contact Plating = Silver

Housing Features:

- UL Flammability Rating = UL 94-HB

Configuration Features:

- Number of Actuators = Single

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:

- Stamped Marking = With

Other:

- Brand = Alcoswitch

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

