





LOC		DIST		REVISIONS					
—		—		P	LTR	DESCRIPTION	DATE	DWN	APVD
					P	REV PER ECO 15-016064	11-9-15	CT	CD



- THIS PLUG WILL MATE WITH ANY RECEPTACLE CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18274-1.
- MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .072 [1.83] DIA.
- BERYLLIUM COPPER RETENTION CLIPS (15) ARE INCLUDED IN INSERT ASSEMBLY.
- CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
- THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311-P-4.
- UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
- CUSTOMER PART NUMBER MAY BE SPLIT BETWEEN FRONT AND REAR SHELL, SAME SIDE. FAR SIDE REFERS TO WIDE SIDE OF KEYSTONE, NEAR SIDE REFERS TO NARROW SIDE OF KEYSTONE.
- RESTRICTED TO CAE ELECTRONICS ONLY.
- CONTACTS FOR 206798-8 ARE UNASSEMBLED.



CONTACT P/N 205089-1
(MIL-39029/64-369)
(SUPPLIED WITH 206798-8 ONLY)
QTY = 15



OBSOLETE

	.120	570513-7	206798-9	206798-9
	.120	B41-P10009-0013	206798-8	206798-8
	.120	311P409-2P-B-12	206798-2	206798-7
	.120	122137P15P	206798-6	206798-6
	.120	2A014-002V-001	206798-4	206798-4
	.154	-	206798-3	206798-3
	.120	311P409-2P-B-12	206798-2	206798-2
	.154	311P409-2P-B-15	206798-1	206798-1
REMARKS	DIA A	INK STAMPED CUSTOMER P/N	INK STAMPED AMP P/N	ASSEMBLY NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T. WIEST 12-9-88	TE Connectivity	
DIMENSIONS: INCHES		CHK A. EMADI 12-11-88		
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0. PLC ± .005 1. PLC ± .005 2. PLC ± .005 3. PLC ± .005 4. PLC ± .005 ANGLES ± .005	PRODUCT SPEC	NAME PLUG FOR PIN CONTACTS SERIES 109, SIZE 2 15 POSITION	
		APPLICATION SPEC		
		WEIGHT		
MATERIAL SEE CALLOUTS	FINISH SEE CALLOUTS	SCALE 4:1	SHEET 1 OF 1	REV P