

4		3		2		1																																																																																																																																																									
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION																																																																																																																																																											
© COPYRIGHT — By —				ALL RIGHTS RESERVED.																																																																																																																																																											
3 STRIPES EQUALLY SPACED FOR COLOR CODE: SEE TABLE SLEEVE BODY 1 7.92 [.312] 0.79 [.031] MIN 7.14 [.281] MIN 18.97 [.747] MAX 23.01 [.906] MAX 4				LOC —		DIST —		REVISIONS																																																																																																																																																							
				P —		LTR —		DESCRIPTION		DATE		DWN		APVD																																																																																																																																																	
						—		SEE SHEET 1		—		—																																																																																																																																																			
								AMP WIRE RANGE																																																																																																																																																							
								SEE TABLE STRANDED																																																																																																																																																							
						1		STAMP AMP APPROX AS SHOWN SEE TABLE BELOW.																																																																																																																																																							
						2		WIRE INSULATION DIA: 1.60–3.30[.063–.130] FOR 16 AWG, 1.98–3.30[.078–.130] FOR 14 AWG.																																																																																																																																																							
						3		TONGUE MATERIAL THK: 0.79±0.05[.031±.002].																																																																																																																																																							
						4		APPLIES FROM EDGE OF METAL WIRE BARREL TO CENTER OF STUD HOLE																																																																																																																																																							
				<table><tr><td>—</td><td>GREEN</td><td>14*</td><td>14</td><td>8</td><td>4.34±0.08[.171±.003]</td><td>100</td><td>LOOSE PIECE, BOX</td><td>9–51864–5</td></tr><tr><td>—</td><td>GREEN</td><td>14*</td><td>14</td><td>10</td><td>5.00±0.08[.197±.003]</td><td>100</td><td>LOOSE PIECE, BOX</td><td>9–51864–1</td></tr><tr><td>—</td><td>GREEN</td><td>14*</td><td>14</td><td>6</td><td>3.68±0.08[.145±.003]</td><td>100</td><td>LOOSE PIECE, BOX</td><td>8–51864–1</td></tr><tr><td>—</td><td>BLUE</td><td>16*</td><td>16</td><td>10</td><td>5.00±0.08[.197±.003]</td><td>100</td><td>LOOSE PIECE, BOX</td><td>7–51864–1</td></tr><tr><td>—</td><td>BLUE</td><td>16*</td><td>16</td><td>6</td><td>3.68±0.08[.145±.003]</td><td>100</td><td>LOOSE PIECE, BOX</td><td>6–51864–1</td></tr><tr><td>M7928/1–50 CLASS 2</td><td>GREEN</td><td>14*</td><td>14</td><td>8</td><td>4.34±0.08[.171±.003]</td><td>5000</td><td>ON TAPE, REEL</td><td>1–51864–7</td></tr><tr><td>M7928/1–51 CLASS 2</td><td>GREEN</td><td>14*</td><td>14</td><td>10</td><td>5.00±0.08[.197±.003]</td><td>5000</td><td>ON TAPE, REEL</td><td>1–51864–5</td></tr><tr><td>M7928/1–42 CLASS 2</td><td>BLUE</td><td>16*</td><td>16</td><td>10</td><td>5.00±0.08[.197±.003]</td><td>5000</td><td>ON TAPE, REEL</td><td>1–51864–3</td></tr><tr><td>M7928/1–40 CLASS 2</td><td>BLUE</td><td>16*</td><td>16</td><td>6</td><td>3.68±0.08[.145±.003]</td><td>5000</td><td>ON TAPE, REEL</td><td>1–51864–2</td></tr><tr><td>M7928/1–50 CLASS 1 & 2</td><td>GREEN</td><td>14*</td><td>14</td><td>8</td><td>4.34±0.08[.171±.003]</td><td>1000</td><td>LOOSE PIECE</td><td>1–51864–1</td></tr><tr><td>M7928/1–41 CLASS 1 & 2</td><td>BLUE</td><td>16*</td><td>16</td><td>8</td><td>4.34±0.08[.171±.003]</td><td>1000</td><td>LOOSE PIECE</td><td>1–51864–0</td></tr><tr><td>M7928/1–51 CLASS 1 & 2</td><td>GREEN</td><td>14*</td><td>14</td><td>10</td><td>5.00±0.08[.197±.003]</td><td>1000</td><td>LOOSE PIECE</td><td>51864–9</td></tr><tr><td>M7928/1–49 CLASS 1 & 2</td><td>GREEN</td><td>14*</td><td>14</td><td>6</td><td>3.68±0.08[.145±.003]</td><td>1000</td><td>LOOSE PIECE</td><td>51864–8</td></tr><tr><td>M7928/1–42 CLASS 1 & 2</td><td>BLUE</td><td>16*</td><td>16</td><td>10</td><td>5.00±0.08[.197±.003]</td><td>1000</td><td>LOOSE PIECE</td><td>51864–7</td></tr><tr><td>M7928/1–40 CLASS 1 & 2</td><td>BLUE</td><td>16*</td><td>16</td><td>6</td><td>3.68±0.08[.145±.003]</td><td>1000</td><td>LOOSE PIECE</td><td>51864–6</td></tr><tr><td>MILITARY P/N AND CLASS</td><td>STRIPE COLOR</td><td>1</td><td>WIRE SIZE</td><td>”B”</td><td>DIM ”A”</td><td>QUANTITY</td><td>PACKAGE TYPE</td><td>PART NO</td></tr></table>												—	GREEN	14*	14	8	4.34±0.08[.171±.003]	100	LOOSE PIECE, BOX	9–51864–5	—	GREEN	14*	14	10	5.00±0.08[.197±.003]	100	LOOSE PIECE, BOX	9–51864–1	—	GREEN	14*	14	6	3.68±0.08[.145±.003]	100	LOOSE PIECE, BOX	8–51864–1	—	BLUE	16*	16	10	5.00±0.08[.197±.003]	100	LOOSE PIECE, BOX	7–51864–1	—	BLUE	16*	16	6	3.68±0.08[.145±.003]	100	LOOSE PIECE, BOX	6–51864–1	M7928/1–50 CLASS 2	GREEN	14*	14	8	4.34±0.08[.171±.003]	5000	ON TAPE, REEL	1–51864–7	M7928/1–51 CLASS 2	GREEN	14*	14	10	5.00±0.08[.197±.003]	5000	ON TAPE, REEL	1–51864–5	M7928/1–42 CLASS 2	BLUE	16*	16	10	5.00±0.08[.197±.003]	5000	ON TAPE, REEL	1–51864–3	M7928/1–40 CLASS 2	BLUE	16*	16	6	3.68±0.08[.145±.003]	5000	ON TAPE, REEL	1–51864–2	M7928/1–50 CLASS 1 & 2	GREEN	14*	14	8	4.34±0.08[.171±.003]	1000	LOOSE PIECE	1–51864–1	M7928/1–41 CLASS 1 & 2	BLUE	16*	16	8	4.34±0.08[.171±.003]	1000	LOOSE PIECE	1–51864–0	M7928/1–51 CLASS 1 & 2	GREEN	14*	14	10	5.00±0.08[.197±.003]	1000	LOOSE PIECE	51864–9	M7928/1–49 CLASS 1 & 2	GREEN	14*	14	6	3.68±0.08[.145±.003]	1000	LOOSE PIECE	51864–8	M7928/1–42 CLASS 1 & 2	BLUE	16*	16	10	5.00±0.08[.197±.003]	1000	LOOSE PIECE	51864–7	M7928/1–40 CLASS 1 & 2	BLUE	16*	16	6	3.68±0.08[.145±.003]	1000	LOOSE PIECE	51864–6	MILITARY P/N AND CLASS	STRIPE COLOR	1	WIRE SIZE	”B”	DIM ”A”	QUANTITY	PACKAGE TYPE	PART NO
—	GREEN	14*	14	8	4.34±0.08[.171±.003]	100	LOOSE PIECE, BOX	9–51864–5																																																																																																																																																							
—	GREEN	14*	14	10	5.00±0.08[.197±.003]	100	LOOSE PIECE, BOX	9–51864–1																																																																																																																																																							
—	GREEN	14*	14	6	3.68±0.08[.145±.003]	100	LOOSE PIECE, BOX	8–51864–1																																																																																																																																																							
—	BLUE	16*	16	10	5.00±0.08[.197±.003]	100	LOOSE PIECE, BOX	7–51864–1																																																																																																																																																							
—	BLUE	16*	16	6	3.68±0.08[.145±.003]	100	LOOSE PIECE, BOX	6–51864–1																																																																																																																																																							
M7928/1–50 CLASS 2	GREEN	14*	14	8	4.34±0.08[.171±.003]	5000	ON TAPE, REEL	1–51864–7																																																																																																																																																							
M7928/1–51 CLASS 2	GREEN	14*	14	10	5.00±0.08[.197±.003]	5000	ON TAPE, REEL	1–51864–5																																																																																																																																																							
M7928/1–42 CLASS 2	BLUE	16*	16	10	5.00±0.08[.197±.003]	5000	ON TAPE, REEL	1–51864–3																																																																																																																																																							
M7928/1–40 CLASS 2	BLUE	16*	16	6	3.68±0.08[.145±.003]	5000	ON TAPE, REEL	1–51864–2																																																																																																																																																							
M7928/1–50 CLASS 1 & 2	GREEN	14*	14	8	4.34±0.08[.171±.003]	1000	LOOSE PIECE	1–51864–1																																																																																																																																																							
M7928/1–41 CLASS 1 & 2	BLUE	16*	16	8	4.34±0.08[.171±.003]	1000	LOOSE PIECE	1–51864–0																																																																																																																																																							
M7928/1–51 CLASS 1 & 2	GREEN	14*	14	10	5.00±0.08[.197±.003]	1000	LOOSE PIECE	51864–9																																																																																																																																																							
M7928/1–49 CLASS 1 & 2	GREEN	14*	14	6	3.68±0.08[.145±.003]	1000	LOOSE PIECE	51864–8																																																																																																																																																							
M7928/1–42 CLASS 1 & 2	BLUE	16*	16	10	5.00±0.08[.197±.003]	1000	LOOSE PIECE	51864–7																																																																																																																																																							
M7928/1–40 CLASS 1 & 2	BLUE	16*	16	6	3.68±0.08[.145±.003]	1000	LOOSE PIECE	51864–6																																																																																																																																																							
MILITARY P/N AND CLASS	STRIPE COLOR	1	WIRE SIZE	”B”	DIM ”A”	QUANTITY	PACKAGE TYPE	PART NO																																																																																																																																																							
AMP INCORPORATED CUSTOMER SERVICE SYSTEMS				MAX RECOMMENDED OPERATING TEMPERATURE: 105°C[221°F] MAX				THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN JR RUTH 27OCT99																																																																																																																																																			
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS				PRODUCT INFORMATION CENTER 1–800–522–6752				VOLTAGE RATING: 300 V MAX				CHK RE HERSEY 27OCT99																																																																																																																																																			
FOR APPLICATION				TOOLING ASSISTANCE CENTER				WIRE RANGE: 16 14				APVD C PRESNELL 27OCT99																																																																																																																																																			
TOOLING INFORMATION				1–800–722–1111				CIRC MIL AREA: 1.42mm² [2800] 2.15mm² [4234]				PRODUCT SPEC																																																																																																																																																			
FOR ORDER ENTRY				1–800–526–5142				STRANDED				APPLICATION SPEC																																																																																																																																																			
								MATERIAL COPPER PER ASTM B–152 SLEEVE, BLUE NYLON				FINISH TIN PLATE PER ASTM B545																																																																																																																																																			
								DIMENSIONS: mm [INCHES]				TOLERANCES UNLESS OTHERWISE SPECIFIED:																																																																																																																																																			
												0 PLC ± – 1 PLC ± – 2 PLC ± 0.20[.008] 3 PLC ± – 4 PLC ± – ANGLES ± –																																																																																																																																																			
												NOT AVAILABLE																																																																																																																																																			
												WEIGHT –																																																																																																																																																			
												CUSTOMER DRAWING																																																																																																																																																			
												SCALE NTS																																																																																																																																																			
												SHEET 2 OF 2																																																																																																																																																			
												REV AC1																																																																																																																																																			
												TE Connectivity																																																																																																																																																			
												NAME																																																																																																																																																			
												TERMINAL, RING TONGUE, I.R., PIDG™, WIRE SIZE, 16–14AWG																																																																																																																																																			
												SIZE																																																																																																																																																			
												CAGE CODE																																																																																																																																																			
												DRAWING NO																																																																																																																																																			
												RESTRICTED TO																																																																																																																																																			
												A300779C–51864																																																																																																																																																			