



△ - MATÉRIA PRIMA CONFORME ESPECIFICAÇÃO IEC 60335
GWT 750°C SEM CHAMA
RAW MATERIAL ACC. TO SPEC. IEC 60335
GWT 750°C WITHOUT FLAME.

△ OBSOLETE PARTS; OBSOLETE
CIS STREAMLINING PER D.RENAUD/D.SINISI

NATURAL	△ PA 6.6 V-0	2	-0
LARANJA		2	-7
MARROM		2	-6
CINZA		2	-5
PRETO		2	-4
AMARELO		2	-3
AZUL		2	-2
VERDE		2	-1
VERMELHO	PA 6.6	2	-0
LARANJA			-9
MARROM			-8
CINZA			-7
PRETO			-6
AMARELO			-5
AZUL			-4
VERDE			-3
VERMELHO TINGIDO			-2
NATURAL	POLIAMIDA 6.6		626 541 - 1

OTHER TREATMENT		FINISH		MATERIAL		PART NUMBER	
CUSTOMER DWG for REFERENCE ONLY				THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION			
B1 ECO-09-026444				© COPYRIGHT 1988 BY AMP DO BRASIL LTDA S.P. ALL INTERNATIONAL RIGHTS RESERVED AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENTS AND/OR PATENTS PENDING.			
B REVISED LE10.0051/05				TOLERANCES UNLESS OTHERWISE STATED DEC. ± 0,4 ANGLES ± 1°			
A1 REVISADO				INS. DIA. RANGE ///			
A REDESENHADO				WIRE RANGE ///			
ISS REVISION RECORD				SCALE ///			
DR CHK DATE				AMP do BRASIL LTDA. São Paulo, Brasil			
APP.				DESCRIPTION 4 WAY FASTIN-ON TAB HOUSING			
				DWG NO A3 C 626 541			
				SHEET 1 of 1			