SPECIFICATION CONTROL DRAWING



_			'XY' = WIRE GAUGE (AWG)									
	Product Revision		Product Dimensions									
	Product Name		øA	øB	øC	øD	øE	øF	L1	L2	K	AWG
			min	min	min	min	min	min	max	max	min	
	D-181-3826-6/9	D	5.20	4.70	4.45	3.95	4.00	1.30	17.00	21.5	150	26
	D-181-3830-6/9	D	(0.205)	(0.185)	(0.175)	(0.155)	(0.160)	(0.055)	(0.670)	(0.850)	(5.900)	30

MATERIALS

1. INSULATION SLEEVES: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.

- 2. SOLDER PREFORMS WITH FLUX:
- SOLDER: TYPE Sn63 per ANSI-J-STD-006.
- FLUX: TYPE ROL1 per ANSI-J-STD-004.
- 3. MELTABLE RINGS: Thermally stabilized thermoplastic. Color: gray.
- 4. GROUND LEAD: MIL-W-81822/13, Solid silver plated copper. AWG XY (see table). Color: white.
- 5. GROUND LEAD: MIL-W-81822/13, Solid silver plated copper. AWG XY (see table). Color: blue.

APPLICATION

- 1. These parts are designed to provide an environment protected coaxial termination on cables, rated for 125°C minimum, meeting the dimensional criteria listed, and having a tin or silverplated shields.
- 2. Temperature range: -55°C to +150°C. Install using Raychem-approved convection or infrared heating tools in accordance with Raychem process standard RCPS-200-36.

For best results, prepare the cable as shown:



tyco Electronics		300 Const	ronics Corporation itution Drive, k, CA. 94025, U.S.A.	Raychem	TITLE: COAXIAL SOLDERSLEEVE DEVICE WITH PRE-INSTALLED LEAD				
UNLESS OTHER INCHES DIMENS			IENSIONS ARE IN MIL N BRACKETS.	DOCUMENT NO.: D-181-38XX-6/9					
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	0.00 N/A 0.0 N/A ROUGH			es the right to amend this sers should evaluate the et for their application.	DATE: Jun. 23,	1998	DOC ISSUE: 3		
DRAWN BY: M. FORONDA		CAGE CODE 06090	: REPLACES: D18138XX	DCR NUMBER: D981033	PROD. REV.: SEE TABLE	SCALE: None	SIZE: A	SHEET: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision.

© 2004 Tyco Electronics Corporation. All rights reserved