

## CC2695P Series

### Dual Wire Coil Cord with Parking Jack

The CC2695-P's polyurethane coil insulation and strain relief molding offers excellent coil memory and endurance. The molded snap head provides a convenient parking jack for the cord when not in use. Two female snaps, a 3.5mm phono plug and 1 meg resistor are standard.

Dual wire wrist straps provide redundancy. When used with resistive loop (dual wire) monitors, the CC2695P wrist strap sets continuously verify resistance to ground.



Parking Jack

#### Product Specifications

##### Coil Cord

Length:	5', 10', and 20' feet, extended
Resistor:	1 meg ohm
Flex Life:	> 20,000 flexes
Color:	Blue, black
Banana:	3.5mm phono plug*

\*Compatibility with particular resistance monitors should be verified.

#### Product Number

<u>Item Number</u>	<u>Description</u>
CC2695P-5	5' dual coil cord, parking jack, 4mm
CC2695P-10	10' dual coil cord, parking jack, 4mm
CC2695P-20	20' dual coil cord, parking jack, 4mm
WB2695P-5	Set, dual band, 5' cord, parking jack, 4mm, 1meg
WB2695P-10	Set, dual band, 10' cord, parking jack, 4mm, 1meg
WB2695P-20	Set, dual band, 20' cord, parking jack, 4mm, 1meg

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.