

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

HDMI over Cat5/6 Extender Kit, Box-Style Transmitter/Receiver for Video/Audio, IR, Up to 125 ft., TAA

MODEL NUMBER: B126-1A1-IR







Transmitter and receiver work in tandem to extend HDMI and IR signals via Cat5e/6 cable to a projector, monitor or television. Ideal for digital signs, trade shows, classrooms, churches, offices and retail settings.

Description

The B126-1A1-IR HDMI over Cat5/6 Active Extender Kit includes a transmitter unit and a receiver unit that work in tandem to extend HDMI audio/video and IR remote control signals to a projector, monitor or television. The kit is ideal for digital signs, trade shows, classrooms, churches, offices, retail settings and other applications where the source is located farther than conventional cables allow.

HDMI cable (see Tripp Lite's P569-Series) connects a local display and the audio/video source to the transmitter unit and a remote display to the receiver unit. Cat5e/6 cable connects the two units (for best results, use 24 AWG solid-wire Cat5e/6 cable, such as Tripp Lite's N202-Series). Included IR-IN and IR-OUT cables allow you to control the video source, such as a Blu-ray™ player, while standing at the remote display.

The B126-1A1-IR can extend a 1080p (60 Hz) signal up to 125 feet. In addition to crystal-clear video, the B126-1A1-IR delivers full, rich stereo and 7.1-channel surround sound (multi-channel or PCM) audio. Built-in equalization control lets you fine-tune the image quality at each remote display. Supports 24-bit True Color (8 bits per channel) and HDCP. Easy to set up with no software or drivers to install. Mounts to a wall, rack or pole using the included hardware.

Features

Extends High-Definition Signals

- Extends a 1080p (60 Hz) signal up to 125 ft.
- IR functionality lets you control your Blu-ray player while standing at the remote display
- Transmitter and receiver connect with one Cat5e/6 cable (for best results, use 24 AWG solid-wire

Highlights

- Supports high-definition video resolutions up to 1080p (60 Hz)
- Supports stereo and 7.1channel surround sound audio
- Included IR cables allow display-side control of video source
- Plug and play—no software or drivers to install
- Built-in equalization control lets you adjust monitor image

System Requirements

Package Includes

- Transmitter unit
- Receiver unit
- IR-IN cable
- IR-OUT cable
- Screwdriver for adjusting equalization
- (2) External power supplies with NEMA 1-15P plugs (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A)
- Mounting hardware
- Owner's manual



Cat5e/6 cable, such as Tripp Lite's N202-Series)

- Supports stereo and 7.1-channel surround sound (multi-channel or PCM) audio
- Supports 24-bit True Color (8 bits per channel) and HDCP
- Built-in equalization control lets you adjust the image on the local monitor

Easy to Set Up and Use

- Plug-and-play engineering—no software or drivers to download and install
- Works with all operating systems and HDMI sources
- Units connect quickly to source and displays with HDMI cable, such as Tripp Lite's P569-Series
- Units install on a wall, rack or pole with the included hardware

TAA-Compliant

• Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
UPC Code	037332191328	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.5A	
External Power Supply Output Specs (V / A)	5V / 2A	
External Power Supply Cord Length (ft.)	4.5	
External Power Supply Cord Length (m.)	1.37	
External Power Supply DC Barrel Connector Specs	OD: 5.5 x 2.1 x 7.5mm, Positive Pin, Negative Sleeve	
External Power Supply Plug(s)	NEMA 1-15P North America	
External Power Supply Certifications	FCC; RoHS; UL; cUL	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Green (Power), Orange (Activity)	
PHYSICAL		
Color	Black	



Included Mounting Accessories	Yes	
Material of Construction	SECC	
Rackmountable	Yes	
Receiver Unit Dimensions (hwd / cm.)	2.6 x 9.2 x 6.4	
Receiver Unit Dimensions (hwd / in.)	1 x 3.6 x 2.5	
Receiver Unit Weight (kg)	0.09	
Receiver Unit Weight (lbs.)	0.2	
Shipping Dimensions (hwd / cm)	21.41 x 16.51 x 5.59	
Shipping Dimensions (hwd / in.)	8.43 x 6.50 x 2.20	
Shipping Weight (kg)	0.82	
Shipping Weight (lbs.)	1.80	
Transmitter Unit Dimensions (hwd / cm.)	2.6 x 9.2 x 6.4	
Transmitter Unit Dimensions (hwd / in.)	1 x 3.6 x 2.5	
Transmitter Unit Weight (kg)	0.09	
Transmitter Unit Weight (lbs.)	0.2	
Unit Packaging Type	Вох	
ENVIRONMENTAL		
Operating Temperature Range	14 to 167 F (-10 to 75 C)	
Storage Temperature Range	-4 to 176 F (-20 to 80 C)	
Relative Humidity	0% to 85%, Non-Condensing	
COMMUNICATIONS		
Signal Range (ft.)	125	
Signal Range (m)	38	
CONNECTIONS		
Side A - Connector 1	(2) HDMI (FEMALE)	
Side A - Connector 2	3.5MM (FEMALE); RJ45 (FEMALE)	
Side B - Connector 1	HDMI (FEMALE)	
Side B - Connector 2	3.5MM (FEMALE); RJ45 (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
FEATURES & SPECIFICATIONS		



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

HDMI Specification	1.4	
HDCP Specification	1.4	
Audio Specification	7.1 Channel Surround Sound (Multi-Channel or PCM)	
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables	
Max Supported Color Depth	24-bit True Color	
IR Remote Extension Support	Yes	
3D Video Supported	Yes	
Technology	HDMI; IR	
STANDARDS & COMPLIANCE		
Certifications	Tested to FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies