

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Dual VGA with Audio over Cat5/Cat6 Extender, Box-Style Receiver, 1440x900 at 60Hz, Up to 300 ft., TAA

MODEL NUMBER: B132-200A-SR







Extends a VGA and audio signal to two sets of monitors and speakers up to 300-ft. from the source

Description

Tripp Lite's B132-200A-SR Dual VGA with Audio over Cat5 Extender Receiver Unit is designed to work with Tripp Lite's B13 and B13 VGA with Audio over Cat5 Extender / Splitter Transmitter Units. Unlike the B13 Receiver Unit (which supports distances up to 1,000-ft.), or the B132-100A-MR (which supports distances up to 750-ft.) the B132-100A-SR is a cost effective solution for distances up to 300-ft. It extends a 1440 x 900 video and audio signal up to 150-ft. from the source, or a 1024 x 768 video and audio signal up to 300-ft. It also features dual VGA and audio ports for the connection of two sets of monitors and speakers. An Equalization control is provided to adjust the video image. Audio connections are made with standard 3.5 (not included). Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Features dual VGA and audio ports for the connection of two sets of monitors and speakers
- Works with a B13 or B13 Transmitter Unit to extend a VGA video and audio signal up to 300-ft. from the source
- Extends a 1440 x 900 video and audio signal up to 150-ft, or a 1024 x 768 video and audio signal up to 300-ft.
- 24AWG, Solid Wire Cat5e/6 cable (such as Tripp Lite's N20 Cat6 cables) is required to achieve maximum distance and resolution
- Features a built-in equalization control to adjust the video image
- All operating systems supported
- Plug and play; no software or drivers required
- HDCP and EDID compliant

Highlights

- Features dual VGA and audio ports for the connection of two sets of monitors and speakers
- Works with a B132-002A-2 or B132-004A-2 Transmitter Unit to extend a VGA video and audio signal up to 300-ft. from the source
- Extends a 1440 x 900 video and audio signal up to 150-ft, or a 1024 x 768 video and audio signal up to 300-ft.
- Plug and play, no software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

Package Includes

- B132-200A-SR
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 4.5 ft.)
- Screwdriver for EQ adjustment
- Owner's Manual



- Ideal for digital signage installations for retail, schools, churches, etc.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
UPC Code	037332185570	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 4.5 ft.	
PHYSICAL		
Color	Black	
Shipping Dimensions (hwd / cm)	5.59 x 15.75 x 18.29	
Shipping Dimensions (hwd / in.)	2.20 x 6.20 x 7.20	
Shipping Weight (kg)	0.50	
Shipping Weight (lbs.)	1.10	
Unit Dimensions (hwd / cm)	2.7 x 11.5 x 6.24	
Unit Dimensions (hwd / in.)	1.1 x 4.5 x 2.5	
Unit Weight (kg)	0.23	
Unit Weight (Ibs.)	0.5	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	300	
Max 480P Range (ft)	300	
Max 1440 x 900 Range (ft)	150	
Max 480i Range (ft)	300	
Max 640 x 480 Range (ft)	300	
Max 800 x 600 Range (ft)	300	
Max 720P Range (ft)	150	
CONNECTIONS		
Ports	2	
Side A - Connector 1	RJ45 (FEMALE)	
Side B - Connector 1	(2) HD15 (FEMALE)	
Side B - Connector 2	(2) 3.5MM (FEMALE)	
FEATURES & SPECIFICATIONS		



Technology	VGA/SVGA; Stereo Audio	
STANDARDS & COMPLIANCE		
Approvals	CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies