



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

## 240V External Battery Pack for Select Tripp Lite UPS Systems, 3U Rack/Tower, TAA

MODEL NUMBER: **BP240V10RT3UTAA**



TAA-compliant external battery pack provides extended runtime for compatible 240V Tripp Lite UPS systems.

### Features

**Gives Your Compatible Tripp Lite UPS System Extended Runtime**The BP240V10RT3UTAA is compatible only with Tripp Lite's SU8000RT3UTAA, SU8000RT3U1TFTAA, SU10000RT3UTAA, SU10000RT3U2TAA, SU16KRATA, SU16KRT-1TFTAA, SU20KRATA, SU20KRT-1TFTAA and other UPS systems that specify the use of this battery pack. Not only does it provide extended runtime, but it can also be daisy-chained using its rear connector to additional external battery packs for even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for simple installation.

**Mounts in 3U of Space in 19 in. 4-Post Racks**This battery pack's multi-use form factor supports stacking or mounting in 3U of space in EIA-standard 19-inch racks using the included 4-post rack-mounting brackets. The BP240V10RT3UTAA is also compatible with Tripp Lite's 2-9USTAND for upright tower configuration and 2POSTRMKITHD for 2-post racks (both accessories sold separately).

**TAA-Compliant for GSA Schedule Purchases**The BP240V10RT3UTAA is compliant with the Federal Trade Agreements Act for GSA Schedule purchases.

**2-Year Warranty and Environmentally Responsible Design**The BP240V10RT3UTAA comes with a 2-year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

### Highlights

- Connects to expandable 240V DC Tripp Lite UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Mounts in 3U of space in 19 in. rack using included 4-post installation hardware
- Supports 2-post rack or tower installation with optional accessories (sold separately)
- Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

- Extends the runtime of your compatible Tripp Lite UPS system
- Daisy-chains to additional battery packs to provide even longer extended-run operation

### System Requirements

- Tripp Lite SU8000RT3UTAA, SU8000RT3U1TFTAA, SU10000RT3UTAA, SU10000RT3U2TFTAA, SU16KRATA, SU16KRT-1TFTAA, SU20KRATA or SU20KRT-1TFTAA UPS system

### Package Includes

- BP240V10RT3UTAA 240V External Battery Pack, 3U Rack/Tower, TAA
- Rack-mounting hardware
- Owner's manual



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Specifications

OVERVIEW	
UPC Code	037332217790
INPUT	
Input Phase	Single-Phase
BATTERY	
Expandable Battery Runtime	Includes a second input/output connector to daisy-chain multiple battery packs
DC System Voltage (VDC)	240
UPS Connection	Detachable cable with UPS specific DC connector (91.4 cm length, 6 gauge)
Typical Battery Lifespan	4-6 years typical (North America)
Expandable Runtime	Yes
PHYSICAL	
External Battery Pack Form Factor	Rack/Tower
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount ( <a href="http://www.tripplite.com/2-Post-Rack-Mount-Installation-Kit-3U-Larger-UPS-Transformer-Battery-Pack-Components~2POSTRMKITHD">2 post rackmount</a> ); Tower ( <a href="http://www.tripplite.com/2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems~2-9USTAND">2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems</a> )
Material of Construction	Black steel cabinet
Minimum Required Rack Depth (cm)	83.82
Minimum Required Rack Depth (inches)	33
Rack Height	3U
Shipping Dimensions (hwd / cm)	29.21 x 58.42 x 83.82
Shipping Dimensions (hwd / in.)	11.50 x 23.00 x 33.00
Shipping Weight (kg)	89.00
Shipping Weight (lbs.)	196.21
Unit Dimensions (hwd / cm)	13.34 x 44.45 x 63.5
Unit Dimensions (hwd / in.)	5.25 x 17.5 x 25
Unit Weight (kg)	71.99
Unit Weight (lbs.)	158.70
STANDARDS & COMPLIANCE	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Certifications	Tested to CE; TAA Compliant
<b>WARRANTY</b>	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>