

BP24V70-3U

External Battery Pack for UPS Systems



Model #: BP24V70-3U

- ▶ Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector
- ▶ Simple installation; 3U rackmount, tower and stack adaptable
- ▶ Supports multi-battery pack installations via built-in daisychain connector
- ▶ 2-year warranty

DESCRIPTION

BP24V70-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Supports the connection of multiple BP24V70-3U battery packs via built-in daisychain connector. Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - SU750RTXL2U, SU1000RTXL2Ua, SMART750RMXL2U and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports multi-battery pack installation via built-in daisychain connector
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

TYPICAL APPLICATIONS

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

OPTIONS & ACCESSORIES

- Tower stands: [2-9USTAND](#)
- 2-Post Mounting Kit: [2POSTRMKITWM](#)
- Extended warranties: 3 Year [WEXT3-BP24V](#), 5 Year [WEXT5-BP24V](#)

PACKAGE INCLUDES

- BP24V70-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

| | |
|----------------------------------|--|
| Connects to UPS via: | Attached cable with red/black 75 amp male DC connector |
| DC system voltage: | 24V DC |
| Typical battery lifespan: | 4-6 years typical (North America) |

PHYSICAL

| | |
|--------------------------------------|--|
| Shipping weight (lbs): | 176.37 |
| Shipping weight (kg): | 80.07 |
| Unit weight (lbs): | 138.89 |
| Unit weight (kg): | 63.06 |
| Unit Dimensions (HWD/in): | 5.25 x 17.5 x 25 |
| Unit Dimensions (HWD/cm): | 13.33 x 44.45 x 63.5 |
| Shipping Dimensions (HWD/in): | 11.25 x 23 x 31.5 |
| Shipping Dimensions (HWD/cm): | 28.56 x 58.42 x 80.01 |
| Material of construction: | Steel |
| Form factors supported: | 3U rackmount in 4 post rack enclosures, supports tower installation with optional 2-9USTAND accessory, supports 2 post rackmount installation with optional 2POSTRMKITWM accessory |

WARRANTY

| | |
|---------------------------|--|
| Product warranty: | 2 year product warranty |
| Optional coverage: | 3 year, 5 year, next day and on-site warranty coverage available |

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.