

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Tripp Lite Waber Industrial Surge Protector, 6-Outlet, 6-ft. Cord, 2100 Joules

MODEL NUMBER: DG115-SI











Highlights

- 6 outlets/6 ft. cord
- 2100 joule rating
- · All metal housing
- Visual surge indication

Package Includes

- DG115-SI Power Strip
- Warranty information
- · Instruction manual

Description

The Waber-by-Tripp Lite DG115-SI Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 2100 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip with lighted power switch

SUPPRESSION - 2100 joules AC suppression

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1449 3rd Edition (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications



	OVERVIEW		
UPC Code	037332101150		
INPUT			
Nominal Input Voltage(s) Supported	120V AC		
Recommended Electrical Service	120V (110-125V)		
Input Cord Gauge Type	14 gauge; SJT		
Voltage Compatibility (VAC)	120		
Maximum Surge Amps	39000		
Input Plug Type	NEMA 5-15P		
Input Cord Length (ft.)	6		
Right-Angle Plug	No		
Input Cord Length (m)	1.83		
Integrated Cord Clip	No		
OUTPUT			
Frequency Compatibility	50 / 60 Hz		
Output (Watts)	1800		
Output Receptacles	(6) 5-15R		
Circuit Breaker (amps)	15		
Overload Protection	15A resettable circuit breaker integrated into lighted power switch		
Transformer Accommodation	(2) Yes		
Right-Angle Outlets	No		
USER INTERFACE, ALERTS & CONTROLS			
Diagnostic LED(s)	Yes		
Switches	Lighted two position power switch controls power to all outlets		
Diagnostic LED Details	Protection present (green)		
SURGE / NOISE SUPPRESSION			
AC Suppression Joule Rating	2100		
AC Suppression Response Time	< 1 ns		
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression		
UL1449 Let Through Rating	400V - UL Verified		
EMI / RFI Filtering	Up to 20 dB		
Immunity	Conforms to IEE 587 / ANSI C62.41		





Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Anti-Microbial Protective Coating	No	
Color	Light Gray	
Color (AC Line Cord)	Light Gray	
Integrated Keyhole Mounting Slots	Yes	
Material of Construction	Metal	
Receptacle Color	White	
Shipping Dimensions (hwd / cm)	6.10 x 36.58 x 14.99	
Shipping Dimensions (hwd / in.)	2.40 x 14.40 x 5.90	
Shipping Weight (kg)	0.95	
Shipping Weight (lbs.)	2.10	
Unit Dimensions (hwd / cm)	31.75 x 6.35 x 3.8	
Unit Dimensions (hwd / in.)	12.5 x 2.5 x 1.5	
SPECIAL FEATURES		
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Canada	cUL	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies