

10GBase CX4 Cable, 3M (10-ft.)

MODEL NUMBER: N263-03M



Description

Tripp Lite's high-speed 10Gbps CX4 cables provide an ultra high performance, cost effective solution for Gigabit Copper applications. Featuring 30AWG Madison TurboTwin twinaxial cable, these cables utilize up to 3.125 gigabytes per second wire speed connections with four channels. Cables work with any manufacturers' 10Gbps Xenpak transceiver that utilize the Ejector style latch connector. Tripp Lite CX4 cables are available in 0.5 meter, 1 meter, and 3 meter lengths.

Features

- Flexible 30AWG Madison TurboTwin Cable
- Ejector style latch mechanism
- Connects the CX4 modules between two switches
- Fully 802.3ak compliant
- RoHS Compliant

Specifications

OVERVIEW	
UPC Code	037332138514
INPUT	
Cable Length (ft.)	9.8
Cable Length (m)	3
PHYSICAL	

Highlights

- Works with any Manufacturers' 10Gb XenPak
- Made with Premium Madison TurboTwin cable
- Compliant with the IEEE Draft specification P802.3ak/D5.3

System Requirements

 Ethernet switches with CX4 / Xenpak modules for 10Gbps linking

Package Includes

• 10 GBase CX4 Cable - 3 Meter



Color	Black	
Shipping Dimensions (hwd / cm)	25.40 x 30.48 x 1.27	
Shipping Dimensions (hwd / in.)	10.00 x 12.00 x 0.50	
Shipping Weight (kg)	0.32	
Shipping Weight (lbs.)	0.70	
CONNECTIONS		
Side A - Connector 1	CX4 [SFF-8470] (MALE)	
Side B - Connector 1	CX4 [SFF-8470] (MALE)	
FEATURES & SPECIFICATIONS		
Technology	CX4	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies