

Power Extension Cord, C19 to C20 - Heavy Duty, 20A, 250V, 12 AWG, 6 ft., Black

MODEL NUMBER: P036-006







C19 to C20 20A heavy-duty extension cable connects high-output devices with C19/C20 power connectors, including blade server chassis.

Features

20A C20-to-C19 Power Cable for Network Devices That Require a Heavy-Gauge ConnectionThis

heavy-duty extension cord features 12 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This cord can be used to connect a server, router, network switch or blade server enclosure to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The six-foot length allows you flexibility in placing equipment with respect to the power outlet.

Highlights

- Recommended for powering servers, routers and other highoutput network devices
- 6 ft. length allows flexibility in placing devices in relationship to AC outlet
- C20 to C19 cord replaces or upgrades standard power cord provided by manufacturer
- Thick 12 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, servers and monitors to a PDU up to 6 ft. away in your data center
- Extend an existing power connection up to 6 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P036-006 C19 to C20 Heavy-Duty Extension Cord, 6 ft., Black

Specifications

| OVERVIEW | |
|----------------|---------------|
| UPC Code | 037332141620 |
| Country/Region | North America |
| INPUT | |



| [| | |
|----------------------------------------|---------------------------|--|
| Maximum Input Amps | 20 | |
| Cable Length (ft.) | 6 | |
| Cable Length (m) | 1.8 | |
| Voltage Compatibility (VAC) | 250 | |
| PHYSICAL | | |
| Color | Black | |
| Number of Conductors | 3 | |
| Power Cord Jacket Type | SJT | |
| Shipping Dimensions (hwd / cm) | 32.51 x 22.61 x 1.27 | |
| Shipping Dimensions (hwd / in.) | 12.80 x 8.90 x 0.50 | |
| Shipping Weight (kg) | 0.50 | |
| Shipping Weight (lbs.) | 1.10 | |
| Wire Gauge (AWG) | 12 | |
| Wire Gauge (OD - mm ²) | 2.08 | |
| CONNECTIONS | | |
| Side A - Connector 1 | IEC-320-C20 | |
| Side B - Connector 1 | IEC-320-C19 | |
| SPECIAL FEATURES | | |
| High Voltage | Yes | |
| Locking Plug | No | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies