

## Power Distribution Unit (PDU) - Accessory adds additional outlet types to dual voltage UPS System

### MODEL NUMBER: PDU6K

#### Description

Tripp Lite's PDU6K AC power distribution unit offers 24 amp, 240/120V capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 2U rackmount installation. Detachable flanges allow user configuration in dozens of potential mounting schemes. Includes 8 outlets total (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R), with NEMA L14-30P input plug. 4 ft. AC input cord.

PLUG/OUTLETS: Input: NEMA L14-30P/Output: 1 L5-30, 1 L5-20, 2 L6-30, 2 L6-20, 2 6-20R ELECTRICAL: 240V AC input, 240/120V AC output FORMAT: Supports 19 in. rackmount (2U), wallmount and under-counter

#### Features

- Corded AC power distribution unit with 8 output receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19

inch rackmount mounting in 2U format

- 4 120V and 4 240V output receptacles (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R)
- 4 ft. AC cord with L14-30 plug-in connection
- Removable plug enables hardwire input connection

# **Specifications**

OVERVIEW		
UPC Code	037332119346	
INPUT		
Input Connection Type	Nema L14-30 input plug, removable for 4 wire hardwire installation	
Voltage Compatibility (VAC)	240	
Input Cord Length (ft.)	4	
Input Cord Length (m)	1.22	
OUTPUT		
Circuit Breaker (amps)	20	
Overload Protection	20A resettable double pole breaker	
PHYSICAL		
Color (AC Line Cord)	Black	
Form Factors Supported	2U rackmount, wallmount, under-counter	

#### Highlights

- 8 outlet PDU system adds 240 and 120V output receptacles to select dual voltage 240/120V UPS systems
- Includes 4 ft. cord with L14-30 plug
- Input plug supports hardwire input connection
- Supports installation in 2U rackmount, wallmount and under-counter applications

#### Package Includes

- PDU6K rackmount power strip
- Instruction manual



Included Mounting Accessories	Recessed rackmount installation brackets
Material of Construction	Sheet metal
Receptacle Color	Black
Shipping Dimensions (hwd / cm)	16.51 x 46.36 x 20.96
Shipping Dimensions (hwd / in.)	6.50 x 18.25 x 8.25
Shipping Weight (kg)	3.63
Shipping Weight (lbs.)	8.00
Unit Dimensions (hwd / cm)	8.9 x 43.8 x 9.5
Unit Dimensions (hwd / in.)	3.5 x 17.25 x 3.75
Unit Weight (kg)	2.83
Unit Weight (lbs.)	6.25
STANDARDS & COMPLIANCE	
Approvals	UL1778 (USA), cUL (Canada), NOM (Mexico)

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies