

#### Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## 7.4kW Single-Phase 230V Basic PDU, 4 C19 Outlets, IEC 309 32A Blue Input, 3.6 m Cord, 1U Rack-Mount

## MODEL NUMBER: PDUH32HV19









Delivers 230V single-phase AC power to multiple loads from a utility outlet, generator or UPS system in a high-density IT environment. Ideal for data centers, server rooms and network wiring closets.

#### Description

The PDUH32HV19 7.4kW Single-Phase 230V Basic PDU is a versatile no-frills unit for data centers, server rooms and network wiring closets. Perfectly suited for high-density IT environments, the PDUH32HV19 features four rear C19 outlets. The IEC 309 32A Blue (2P+E) input plug with 3.6 m cord connects to your facility's compatible AC power source, generator or protected UPS to distribute power to connected equipment.

The switchless design prevents an accidental shutdown, which could lead to costly downtime. Dual 20A circuit breakers protect connected equipment from dangerous overloads. The reversible all-metal housing supports a variety of mounting options, including 1U horizontal or 0U vertical mounting in EIA-standard 19-inch racks, under a counter or on a wall or workbench.

### Features

#### Reliable Single-Phase 32A 230V Power Distribution

- Ideal no-frills PDU for data centers, server rooms and network wiring closets
- 4 rear C19 outlets
- IEC 309 32A Blue (2P+E) input with 3.6 m power cord
- Rear-panel grounding lug
- Dual 20A circuit breakers protect against overloads

#### Switchless Design

· Prevents accidental shutdowns and costly downtime

## Highlights

- IEC 309 32A Blue (2P+E) input with 3.6 m power cord
- 4 rear C19 outlets
- Switchless design prevents accidental shutdown
- Reversible all-metal housing
- Dual 20A circuit breakers
  protect against overloads

#### Package Includes

- PDUH32HV19 7.4kW Single-Phase 230V Basic PDU
- Mounting hardware
- Owner's manual



#### Versatile Installation Options

- Reversible all-metal housing faces front or rear in rack
- Supports 1U horizontal or 0U vertical mounting in EIA-standard 19 in. racks
- Also mounts on wall, workbench or under a counter

# **Specifications**

| OVERVIEW                          |  |  |
|-----------------------------------|--|--|
| UPC Code                          | 037332183200   |  |
| РДИ Туре                          | Basic  |  |
| INPUT                             |  |  |
| PDU Input Voltage                 | 200; 208; 220; 230; 240  |  |
| Recommended Electrical Service    | 32A 230V   |  |
| Maximum Input Amps                | 32   |  |
| PDU Plug Type                     | IEC-309 32A BLUE (2P+E)  |  |
| Input Phase                       | Single-Phase   |  |
| Input Cord Length (ft.)           | 12   |  |
| Input Cord Length (m)             | 3.66   |  |
| OUTPUT                            |  |  |
| Frequency Compatibility           | 50 / 60 Hz   |  |
| Output Capacity Details           | 7.7kW (240V), 7.4kW (230V), 7kW (220V), 6.4kW (200V) / 32A total capacity; 16A max per breakered outlet bank; 16A max per C19 outlet |  |
| Output Receptacles                | (4) C19  |  |
| Output Nominal Voltage            | 200; 220; 230; 240   |  |
| Overload Protection               | Two 20A circuit breakers protect 2 outlets each  |  |
| USER INTERFACE, ALERTS & CONTROLS |  |  |
| Switches                          | n/a  |  |
| PHYSICAL                          |  |  |
| Form Factors Supported            | 1U rackmount, 0U vertical mount, wallmount and under-counter   |  |
| Material of Construction          | Metal  |  |
| Minimum Device Depth (cm)         | 17.27  |  |
| Minimum Device Depth (in.)        | 6.8  |  |



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

| Minimum Device Depth (mm)              | 173   |
|--|---|
| PDU Form Factor                        | Horizontal (1U)                             |
| Shipping Dimensions (hwd / cm)         | 7.62 x 51.44 x 28.58                        |
| Shipping Dimensions (hwd / in.)        | 3.00 x 20.25 x 11.25                        |
| Shipping Weight (kg)                   | 3.21  |
| Shipping Weight (lbs.)                 | 7.07  |
| Unit Dimensions (hwd / cm)             | 4.5 x 44.5 x 9.53                           |
| Unit Dimensions (hwd / in.)            | 1.75 x 17.5 x 3.75                          |
| Unit Weight (kg)                       | 2.87  |
| Unit Weight (Ibs.)                     | 6.32  |
| ENVIRONMENTAL                          |   |
| Storage Temperature Range              | -30°C to +50°C (-22°F to +122°F)            |
| Relative Humidity                      | 5 to 95% non-condensing                     |
| SPECIAL FEATURES                       |   |
| TVSS Grounding                         | Rear grounding lug                          |
| STANDARDS & COMPLIANCE                 |   |
| Certifications                         | Tested to CE (EN 60950-1), CE Class A, RoHS |
| WARRANTY                               |   |
| Product Warranty Period<br>(Worldwide) | 2-year limited warranty                     |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies