

3.2-3.8kW Single-Phase Metered PDU, 200-240V (8 C13 & 2 C19), C20 / L6-20P Adapter, 12ft Cord, 1U Rack-Mount, TAA

MODEL NUMBER: PDUMH20HV



Description

Tripp Lite Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital meter. Enables visual current monitoring of PDU output current to prevent circuit overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Features

- 16/20A single phase 200-240V Metered Power Distribution Unit / PDU (Agency de-rated to 16A continuous)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- C20 inlet with C20 input cable and L6-20P adapter; 12 ft. / 3.7m line cord
- 1U horizontal rackmount format installs in one rack space
- 10 total outlets (8 C13 / 2 C19)
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Optional PDUSIDEBRKT enables 0U vertical rackmount in compatible racks
- Back panel grounding lug
- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases

Specifications

Highlights

- Metered single phase 16/20A 200-240V PDU
- 1U horizontal rackmount; Digital current meter
- C20 input with L6-20P plug adapter; 12 ft. / 3.7m line cord
- 10 total outlets (8 C13, 2 C19)
- Reversible housing; 6.5 in. / 16.5 cm depth
- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases

Package Includes

- Rackmount PDU
- C19 to L6-20P plug adapter
- Rack mounting brackets



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| OVERVIEW | |
|--------------------------------------|--|
| UPC Code | 037332159014 |
| PDU Type | Metered |
| INPUT | |
| PDU Input Voltage | 200; 208; 220; 230; 240 |
| Recommended Electrical Service | 20A 208/240V; 16A 230V |
| Maximum Input Amps | 20 |
| Maximum Input Amps Details | Agency de-rated to 16A continuous |
| PDU Plug Type | NEMA L6-20P; IEC-320 C20 |
| Input Phase | Single-Phase |
| Input Cord Details | Includes 12 ft. / 3.6m C19 to C20 power cable and L6-20P plug adapter |
| Input Cord Length (ft.) | 12 |
| Input Cord Length (m) | 3.66 |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output Capacity Details | 3.84kW (240V), 3.68kW (230V), 3.52kW (220V), 3.33kW (208V), 3.2kW (200V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet |
| Output Receptacles | (8) C13; (2) C19 |
| Output Nominal Voltage | 200; 208; 220; 230; 240 |
| Overload Protection | n/a |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LCD Display | Digital display reports total PDU output current in amps |
| Switches | n/a |
| PHYSICAL | |
| Form Factors Supported | 1U rackmount. Includes mounting accessories for 2-4 post racks |
| Material of Construction | Metal |
| Minimum Device Depth (cm) | 25.40 |
| Minimum Device Depth (in.) | 10 |
| Minimum Device Depth (mm) | 254 |
| Minimum Required Rack Depth (cm) | 24.13 |
| Minimum Required Rack Depth (inches) | 9.5 |
| PDU Form Factor | Horizontal (1U) |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|--|
| Shipping Dimensions (hwd / cm) | 5.59 x 29.46 x 51.82 |
| Shipping Dimensions (hwd / in.) | 2.20 x 11.60 x 20.40 |
| Shipping Weight (kg) | 3.40 |
| Shipping Weight (lbs.) | 7.50 |
| Unit Dimensions (hwd / cm) | 2,87 x 44,4 x 16,5 |
| Unit Dimensions (hwd / in.) | 1.75 x 17.5 x 6.5 |
| Unit Weight (kg) | 3.08 |
| Unit Weight (lbs.) | 6.80 |
| ENVIRONMENTAL | |
| Storage Temperature Range | -30°C to +50°C (-22°F to +122°F) |
| Relative Humidity | 5-95% non-condensing |
| SPECIAL FEATURES | |
| TVSS Grounding | Rear grounding lug |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to UL 60950-1 (USA, Canada), Class A (Emissions), NOM (Mexico), CE (IEC 60950), RoHS compliant, TAA compliant |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>