

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

3000W Heavy-Duty Mobile Power Inverter with 4 AC/2 USB - 2.0A/Battery Cables

MODEL NUMBER: PINV3000



Converts 12V DC power from your vehicle's battery into 120V AC and 5V DC power to operate and charge electronics while on the road.

Features

Heavy-Duty Power Inverter Charges and Powers Multiple Electronic Devices in Your VehicleYou don't have to be near your computer or an AC power source to keep your mobile devices fully charged and your power tools and small appliances operating. This 3000W mobile inverter converts 12V DC power from your car, truck, fleet vehicle, boat or RV's battery into standard 120V AC power. Just connect the included battery cables between the inverter's DC input terminals and the positive and negative terminals on your vehicle's battery.

4 GFCI-Protected AC Outlets Provide Portable Power for Your Mobile ApplicationsThis power inverter provides a modified sine wave for use at remote locations, such as campgrounds, construction sites and mobile offices. Four NEMA 5-15/20R outlets deliver a continuous output of 3000 watts and a peak output of 6000 watts. That's plenty to operate a variety of appliances and power tools, such as low-power lights, camping accessories, battery chargers for small battery-operated power tools, and mobile office equipment. All outlets have OSHA-compliant GFCI (Ground-Fault Circuit Interrupter) protection to shield you from electrical hazards in case of excessive fault current.

USB Charging Ports Keep Your Devices at Full StrengthTwo USB-A charging ports share 2 amps of charging capacity and remain active even when the inverter's on/off switch is set to Off. This allows you to charge your smartphone, tablet, laptop, MP3 player or GPS unit without draining too much power from the vehicle's battery.

Includes the Latest Safety Features to Protect Your Equipment and BatteryAn on/off switch offers one-touch control over all AC outlets. If the power input from the vehicle's battery drops below 10 volts or exceeds 16 volts, the mobile power inverter will automatically shut down. Green and red LEDs indicate normal and improper operation. The temperature controlled fans begin cooling automatically when the internal temperature rises to a certain level during extended use. An audible alarm sounds during excessively high or low voltage conditions.

Remote Control Panel Allows Power Control from 20 ft. AwayA remote panel is included to extend on/off control over AC power output from a remote location. The wired panel connects to the PINV3000's RJ11 port and can be permanently installed inside your vehicle with user-supplied hardware. This allows you to mount the inverter somewhere out of sight, like inside compartment or cabinet, and be able to operate it from your vehicle's dashboard. The panel's green LED confirms the inverter is powered on. Brackets Included for Permanent MountingThe heavy-duty power inverter's durable aluminum housing is designed to withstand the rigors of road trips, campouts, business trips and family vacations. Use the built-in mounting brackets and your own hardware to install the inverter permanently in a horizontal position.

Highlights

- Provides portable power for mobile devices, including phones and laptops
- Ideal for areas without regular power outlets, such as campsites or construction sites
- Four 5-15/20R GFCI outlets deliver continuous output of 3000W for powering devices
- Two USB charging ports supply 2A to keep smartphones and tablets at full capacity
- Rugged aluminum housing built to withstand rigors of travel and outdoor use

Applications

 Power multiple electronic devices and tools from your car, truck, fleet vehicle, boat or RV

Package Includes

- PINV3000 3000W Heavy-Duty Mobile Car Inverter
- PINVRM wired remote panel w/20 ft. cable
- Battery cable, red/black, 3 ft.
- Grounding cable, 3 ft.
- Owner's manual



Specifications

OVERVIEW		
UPC Code	037332225153	
INPUT		
Recommended Electrical Service	12VDC	
Input Connection Type	DC terminal posts for battery cables with ring terminals	
Voltage Compatibility (VDC)	12V	
Input Cord Length (ft.)	3	
Input Cord Length (m)	0.91	
OUTPUT		
Charging Ports / Amps	(2) 2A	
Frequency Compatibility	60 Hz	
Output Receptacle Details	The four GFCI protected outlets support 15A or 20A equipment plugs.	
Pure Sine Wave Output	No	
Nominal Output Voltage(s) Supported	115V; 120V	
Output Receptacles	(4) 5-15/20R	
Continuous Output Capacity (Watts)	3000	
Peak Output Capacity (Watts)	6000	
Output Voltage Regulation	Maintains PWM sine wave output voltage of 120VAC (+/- 10%)	
Output Frequency Regulation	60 Hz (+/- 3 Hz)	
Overload Protection	YES	
BATTERY		
Expandable Battery Runtime	User-Supplied 12VDC battery system	
DC System Voltage (VDC)	12	
Battery Access	Terminal Post	
Battery Pack Accessory (Optional)	User-Supplied, <a class="productLink" href="//www.tripplite.com/12VDC-Sealed-Maintenance-Free-Battery-
All-Inverter-Chargers-12VDC-Battery-Connections~98-121">98-121 , BP260	
USER INTERFACE, ALERTS & CONTROLS		
Front Panel LEDs	Single multi-color status LED for operation (Green) and fault conditions (RED), GFCI protection status LED (Green); PINVRM connection status LED (Green); GFCI status LEDS (Green)	
Switches	Inverter: ON/OFF/REMOTE Rocker Switch; Optional PINVRM wired remote panel: ON/OFF push-button switch.	
Audible Alarm	Low Battery, Short Circuit, Over-temperature, High DC Voltage, Low DC Voltage and Overload protection	



PHYSICAL		
Cooling Method	Temperature Controlled Fans	
Form Factors Supported	Horizontal Floor or Horizontal Wallmount	
Housing Color	SKY BLUE	
Material of Construction	Aluminium/Steel	
Receptacle Color	White	
Unit Dimensions (hwd / cm)	11.68 x 26.59 x 36.60	
Unit Dimensions (hwd / in.)	4.60 x 10.47 x 14.41	
Unit Weight (kg)	5.12	
Unit Weight (Ibs.)	11.290	
ENVIRONMENTAL		
Relative Humidity	10-90% NON-CONDENSING	
Operating Temperature	0C-40C (32F - 104F)	
SPECIAL FEATURES		
TVSS Grounding	Grounding lug grounds the inverter to vehicle or earth ground; ground cable included	
STANDARDS & COMPLIANCE		
Certifications	Tested to UL458:2015 6TH EDITION; CAN/CSA-C22.2 NO.107.1:2016 4TH EDITION	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	
Optional Coverage	1-Year standard warranty extension	
Extended Warranties	WEXT1E	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies