

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

UL1363a, Paragraph 14.1(d) States "The SPRPT shall be permanently attached to the medical equipment by a means such that it is only removable with the use of a tool." To achieve compliance, one must use the PSCLAMP.

For Patient-Care Vicinity – UL 1363A Medical-Grade Power Strip with 4 15A Hospital-Grade Outlets, 2 ft. Cord

MODEL NUMBER: PS-402-HG-OEM









Supplies power to movable plug-connected components mounted to IV poles, mobile carts, crash carts and mobile medical workstations in operating rooms and patient-care vicinities.

Description

The PS-402-HG-OEM Medical-Grade Power Strip supplies power to movable plug-connected components mounted to a rack, table or pedestal in operating rooms, patient-care vicinities, therapy rooms, imaging environments and administrative areas. Compliant with UL 1363A specifications, this 120V, 50/60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and four NEMA 5-15R-HG hospital-grade outlets.

The power strip is protected by a patented antimicrobial powder coating with EPA-registered and FDA-compliant silver ionic technology. The antimicrobial surface protection is 99.9 percent effective in inhibiting the growth of bacteria, such as C. diff and MRSA, and reducing the risk of HAIs in hospitals and other medical environments. The coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

Two built-in resettable 15A circuit breakers control power to all outlets and protect the power strip against overloads. Switchless design prevents the unit from being accidentally shut off. The 2 ft. power cord eliminates excess cordage that needs to be wrapped.

Mounting tabs and flanges let you install the PS-402-HG-OEM on a wide variety of surfaces, such as IV poles, mobile carts, crash carts and mobile medical workstations. The all-metal housing ensures safety and is guaranteed to last a long time in demanding environments.

Features

Power Distribution Anywhere in Any Medical Facility

- Ideal for use in operating rooms, patient-care vicinities, therapy rooms, imaging environments and administrative areas
- For use on IV poles, mobile carts, crash carts and mobile workstations, when properly mounted

Highlights

- Patented antimicrobial coating
 99.9% effective in inhibiting
 bacteria and viruses
- Approved for use in patient-care vicinities when properly mounted
- Complies with UL 1363A specifications
- Features 4 NEMA 5-15R-HG hospital-grade outlets
- Includes 2 ft. cord with NEMA 5-15P-HG hospital-grade plug

Package Includes

- PS-402-HG-OEM UL 1363A
 Medical-Grade Power Strip with
 4 15A Hospital-Grade Outlets
 and 2 ft. Cord
- Owner's Manual with maintenance requirements



• 120V, 50/60 Hz power strip complies with UL 1363A specifications

Exclusive, Patented Antimicrobial Protection

- Silver ionic powder coating is 99.9% effective in inhibiting the growth of bacteria like C. diff and MRSA
- Patented coating helps to reduce the risk of healthcare-acquired infections (HAIs) in hospitals and other medical environments
- Coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

Versatile Medical-Grade Solution

- 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power
- 2 ft. power cord eliminates excess cordage that needs to be wrapped up
- Rugged, all-metal housing for long life in demanding environments

Premium Safety Features

- Dual, resettable built-in 15A circuit breakers protect against dangerous overloads
- · Switchless design prevents accidental shut-off

Ready to Use Right Out of the Box

• Built-in mounting tabs and flanges make the PS-402-HG-OEM easy to install on a variety of surfaces

Specifications

OVERVIEW		
UPC Code	037332147998	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A, 120V	
Input Plug Features	Hospital Grade Plug	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P-HG	
Input Cord Length (ft.)	2	
Input Cord Length (m)	0.61	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	





Output (Watts)	1800	
Output Receptacles	(4) 5-15R-HG	
Circuit Breaker (amps)	15	
Overload Protection	2 x 15amp breakers (1 line, 1 neutral)	
Transformer Accommodation	(2) Yes	
Outlet Orientation	Single row of 4	
Right-Angle Outlets	No	
LICED INTERFACE ALERTS & CON	The Le	
USER INTERFACE, ALERTS & CON		
Switches	No power switch	
PHYSICAL		
Anti-Microbial Protective Coating	Yes	
Color	White	
Color (AC Line Cord)	White	
Form Factors Supported	IV poles, mobile carts, crash carts and mobile medical workstations	
Included Mounting Accessories	Mounting tabs and flanges	
Integrated Keyhole Mounting Slots	Yes (Includes flanges)	
Keyhole Slot Mounting Measurement (Center to Center)	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm	
Material of Construction	Metal	
Outlets Measurement (Center to Center)	Inner outlets = 32.5mm	
Receptacle Color	White	
Shipping Dimensions (hwd / cm)	5.99 x 15.49 x 24.79	
Shipping Dimensions (hwd / in.)	2.36 x 6.10 x 9.76	
Shipping Weight (kg)	0.74	
Shipping Weight (lbs.)	1.64	
Unit Dimensions (hwd / cm)	4.39 x 6.35 x 21.7	
Unit Dimensions (hwd / in.)	1.73 x 2.50 x 8.54	
Unit Weight (kg)	0.66	
Unit Weight (lbs.)	1.45	
SPECIAL FEATURES		
Built-in Cable Management	No	
STANDARDS & COMPLIANCE		
Approvals	TUV tested to UL 1363A	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies