

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Power Strip - Agency-Approved Hospital/Medical Outlet Strip

MODEL NUMBER: PS-615-HGULTRA



Description

Providing 15A capacity AC power distribution in a rugged all-metal outlet strip for 120V applications, Tripp Lite's PS-615-HGULTRA Power Strip is agency approved for use in physicians' offices, imaging centers, laboratories and medical facilities. Features include 6 hospital-grade receptacles with GFCI protection, 15-foot AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: Incorporates NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospitalgrade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A FORMAT: All-metal corded multi-outlet strip

Features

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade output receptacles (2 with GFCI protection)
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges.
- · Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz electrical compatibility
- Tested to UL (USA) and cUL (Canada)
- · Agency approved for use in medical facilities

Specifications

OVERVIEW	
UPC Code	037332123268

Highlights

- Versatile power distribution strip
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker
- Double-fault safety protection

Package Includes

- PS-615-HGULTRA Power Strip
- User manual with warranty information



INPUT		
Recommended Electrical Service	15A 120V	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P-HG	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.57	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
Overload Protection	15A circuit breaker	
Transformer Accommodation	(3) Yes	
Outlet Orientation	Single row of 6	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Switches	No power switch	
PHYSICAL		
Anti-Microbial Protective Coating	No	
Color	White	
Color (AC Line Cord)	White	
Integrated Keyhole Mounting Slots	Yes (Includes flanges)	
Material of Construction	Metal	
Receptacle Color	White	
Shipping Dimensions (hwd / cm)	5.72 x 38.10 x 15.24	
Shipping Dimensions (hwd / in.)	2.25 x 15.00 x 6.00	
Shipping Weight (kg)	1.61	
Shipping Weight (lbs.)	3.55	
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4	
Unit Dimensions (hwd / in.)	1.5 x 13.75 x 2.5	
Unit Weight (kg)	1.09	
Unit Weight (lbs.)	2.4	



STANDARDS & COMPLIANCE		
Canada	TUV tested to CAN/CSA C22.2 No. 21-95	
UL1363 (Power Tap)	TUV tested to UL1363	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies