

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773 869 12

Telephone: 773.869.1234 www.tripplite.com

1U Rack-Mount Power Strip, 120V, 20A, L5-20P, 12 Outlets (6 Front-Facing, 6-Rear-Facing) 15-ft. Cord

MODEL NUMBER: RS-1215-20T





Highlights

- Designed for standard 19-in.
 racks (1U high)
- 12 NEMA5-15/20R outlets (6 front/6 rear)
- 15-ft. cord with locking NEMA
 L5-20P input plug
- 20A circuit breaker

Description

Tripp Lite's RS-1215-20T Power Strip offers 20A capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19-in. rack meeting EIA standards. Unfiltered electrical pass-through makes RS-1215-20T ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 NEMA5-15/20R outlets (6 front/6 rear), 15-ft. AC power cord with locking NEMA L5-20P input plug and lighted switch with cover that prevents risk of accidental turn-off.

PLUG/OUTLETS: Input: NEMA L5-20P Output: 12 x NEMA5-15/20R (6 front/6 rear) ELECTRICAL: 120V AC, 50/60Hz, 20A (Requires NEMA 5-20R wall receptacle) FORMAT: 19-in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19-in. rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 x NEMA5-15/20R output receptacles (6 front/6 rear)
- 15-ft. AC cord with NEMA L5-20P input plug
- Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn-off
- 20A electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications



INPUT Nominal Input Voltage(s) Supported 120V Recommended Electrical Service 20A 1 Voltage Compatibility (VAC) 120	120V dedicated line MA L5-20P 60 Hz
Nominal Input Voltage(s) Supported 120V Recommended Electrical Service 20A 1 Voltage Compatibility (VAC) 120 Input Plug Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 66	120V dedicated line MA L5-20P 60 Hz
Nominal Input Voltage(s) Supported 120V Recommended Electrical Service 20A 1 Voltage Compatibility (VAC) 120 Input Plug Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 66	120V dedicated line MA L5-20P 60 Hz
Recommended Electrical Service 20A 1 Voltage Compatibility (VAC) 120 Input Plug Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 66	120V dedicated line MA L5-20P 60 Hz
Voltage Compatibility (VAC) Input Plug Type Input Cord Length (ft.) Input Cord Length (m) Integrated Cord Clip No OUTPUT Frequency Compatibility 120 NEMA 4.57 No 50 / 66	MA L5-20P 60 Hz
Input Plug Type Input Cord Length (ft.) Input Cord Length (m) Input Cord Clip No OUTPUT Frequency Compatibility NEMA 4.57 No	60 Hz
Input Cord Length (ft.) Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 66	60 Hz
Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 66	60 Hz
OUTPUT Frequency Compatibility No 50 / 60	60 Hz
OUTPUT Frequency Compatibility 50 / 66	
Frequency Compatibility 50 / 6	
Output (Watts) 2400	
 	5-15/20R
Output Receptacles (12) 5	· · · · · · ·
Circuit Breaker (amps) 20	
Overload Protection 20A c	circuit breaker
Transformer Accommodation (5) Ye	/es
Right-Angle Outlets No	
USER INTERFACE, ALERTS & CONTROLS	
Switches Lighte	ted power switch
Locking Switch Cover Yes	
PHYSICAL	
Anti-Microbial Protective Coating No	
Color Black	k
Color (AC Line Cord) Black	k
Form Factors Supported 1U rac	ackmount, wallmount
Included Mounting Accessories Rackr	kmount flanges
Integrated Keyhole Mounting Slots No	
Material of Construction Metal	al
Outlets Measurement (Center to Center)	ance between Front outlets = 51.6mm; Distance between Rear outlets = 71.1mm
Receptacle Color Black	k
Shipping Dimensions (hwd / cm) 23.62	2 x 6.60 x 51.31



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

9.30 x 2.60 x 20.20	
2.68	
5.90	
4.3 x 44.4 x 11.4	
1.75 x 17.5 x 4.5	
2.45	
5.4	
STANDARDS & COMPLIANCE	
UL-recognized (USA)/cUR (Canada)	
WARRANTY	
Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies