

External SAS Cable, 4 Lane - mini-SAS (SFF-8088) to mini-SAS (SFF-8088), 2M (6 ft.)

MODEL NUMBER: \$524-02M



Description

Tripp Lite's S524-02M External SAS cable features SFF-8088 to SFF-8088 "mini-SAS" connectors with heavy- duty metal backshells. This 4-channel Infiniband cable is constructed with high-performance cable, which features individually shielded parallel pairs, double EMI/RFI shielding, and 6.0 Gigabytes per second performance.

Features

- 2-meter External SAS Cable, SFF-8088 to SFF-8088
- Made with High-Performance Infiniband Cable
- Support data rates from 3.0 up to 6.0 gigabytes per second
- SFF-8088 connectors in diecast zinc housing for durability
- · RoHS compliant

Specifications

OVERVIEW		
UPC Code	037332151995	
INPUT		
Cable Length (ft.)	6.6	
Cable Length (m)	2	
PHYSICAL		

Highlights

- High-performance 2-meter SAS
 external cable
- Mini-SAS SFF-8088 (iSAS) to

Mini-SAS SFF-8088 (iSAS)

System Requirements

- SAS Controllers, SAS Chassis,
- SAS/SATA Hard Drives

Package Includes

2-Meter SAS External, SFF-8088 to SFF-8088 Cable



[
Color	Black	
Shipping Dimensions (hwd / cm)	13.46 x 9.91 x 1.27	
Shipping Dimensions (hwd / in.)	5.30 x 3.90 x 0.50	
Shipping Weight (kg)	0.06	
Shipping Weight (lbs.)	0.14	
CONNECTIONS		
Side A - Connector 1	SFF-8088	
Side B - Connector 1	SFF-8088	
FEATURES & SPECIFICATIONS		
Technology	SAS	
STANDARDS & COMPLIANCE		
Certifications	ROHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies