

## Protect It! 6-Outlet Surge Protector, 4-ft. Cord, 540 Joules - Accommodates 2 Transformers

MODEL NUMBER: TLP64



### Highlights

- 6 outlets / 4 ft cord
- 540 joule rating
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Package Includes

- TLP64
- Instruction manual with warranty information

### Description

Tripp Lite's TLP64 offers economical AC surge suppression for protection of workstations, desktop PCs, point-of-sale terminals and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP64 offers 6 total outlets, 4 foot cord and diagnostic LEDs to warn of suppressor damage. AC suppression rated at 540 joules shields equipment from surges and line noise. Attractive gray suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- 6 outlets with integrated child safety covers
- 4ft cord
- Surge suppression rating: 540 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present and ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## Specifications

### OVERVIEW



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|  |  |
|--|--|
| UPC Code                                     | 037332159694   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 60 Hz  |
| Output (Watts)                               | 1800   |
| Output Receptacles                           | (6) 5-15R  |
| Circuit Breaker (amps)                       | 15   |
| Overload Protection                          | 15A resettable illuminated combo switch / circuit breaker                          |
| Transformer Accommodation                    | (4) Yes  |
| Outlet Orientation                           | Block style 2 rows of 3 outlets  |
| Right-Angle Outlets                          | No   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Cord Gauge Type                        | 14 gauge; SJT  |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 36000  |
| Input Plug Type                              | NEMA 5-15P   |
| Input Cord Length (ft.)                      | 4  |
| Right-Angle Plug                             | No   |
| Input Cord Length (m)                        | 1.22   |
| Integrated Cord Clip                         | No   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Diagnostic LED(s)                            | Yes  |
| Switches                                     | Combination AC circuit breaker and 2 position red illuminated on/off power switch  |
| Diagnostic LED Details                       | Built-in LED confirms suppressor "protection present" (green) status               |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 540  |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| Clamping Voltage (RMS)                       | 150  |
| UL1449 Let Through Rating                    | 400v   |
| EMI / RFI Filtering                          | Up to 40 dB  |
| Automatic Shut-Off                           | Yes  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| DATALINE SURGE SUPPRESSION                           |  |
|--|--|
| Telephone/DSL Protection                             | No   |
| Cable (Coax) Protection                              | No   |
| Network (Ethernet) Protection                        | No   |
| PHYSICAL   |  |
| Anti-Microbial Protective Coating                    | No   |
| Color  | Light Gray   |
| Color (AC Line Cord)                                 | Light Gray   |
| Housing Color  | Light Gray   |
| Integrated Keyhole Mounting Slots                    | Yes  |
| Keyhole Slot Mounting Measurement (Center to Center) | 119mm  |
| Material of Construction                             | Plastic  |
| Outlets Measurement (Center to Center)               | Distance between standard outlets = 28.5mm; Distance between standard outlet and transformer outlet = 48.5mm |
| Receptacle Color                                     | Gray   |
| Shipping Dimensions (hwd / cm)                       | 29.72 x 4.44 x 18.29   |
| Shipping Dimensions (hwd / in.)                      | 11.70 x 1.75 x 7.20  |
| Shipping Weight (kg)                                 | 0.64   |
| Shipping Weight (lbs.)                               | 1.40   |
| Unit Dimensions (hwd / cm)                           | 3.81 x 10.74 x 21.06   |
| Unit Dimensions (hwd / in.)                          | 1.50 x 4.23 x 8.29   |
| Unit Weight (kg)                                     | 0.50   |
| Unit Weight (lbs.)                                   | 1.10   |
| SPECIAL FEATURES                                     |  |
| Rotatable Outlets                                    | No   |
| CERTIFICATIONS                                       |  |
| UL1449 3rd Edition (AC Suppression)                  | UL1449 3rd Edition   |
| UL1363 (Power Tap)                                   | UL1363   |
| Canada   | cUL  |
| Approvals  | Exceeds IEEE 587 category A&B specifications   |
| WARRANTY   |  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |   |
|---|---|
| Product Warranty Period<br>(Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$20,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>