

## USB 3.0 SuperSpeed to 2.5 in. SATA III Encrypted Hard Drive Enclosure with Keypad Lock and UASP Support

MODEL NUMBER: U357-025-SEC



Password-protected enclosure connects a 2.5 in. SATA hard disk drive or solid state drive to your computer's USB 3.0 port for extra storage and fast data transfer. UASP-enabled for 70% more speed with UASP host controller.

### Description

The U357-025-SEC USB 3.0 SuperSpeed to 2.5 in. SATA Encrypted Hard Drive Enclosure is a quick, easy way to connect a SATA HDD (Hard Disk Drive) or SSD (Solid State Drive) to your laptop, netbook or notebook's USB 3.0 port.

In addition, it provides state-of-the-art real-time 256-bit AES encryption to ensure all data stored on the SATA drive is for your eyes only. A secure keypad lock provides password security for secret documents and files. If the enclosure is lost or stolen, your data remains protected. Change your custom password as often as you like.

Perfect for portable storage or backing up sensitive data, the compact enclosure is compatible with 2.5-inch SATA drives up to 2 TB (and will support larger drives when available). It supports USB 3.0 data transfer rates up to 5 Gbps. It also reads data up to 70 percent faster and writes up to 40 percent faster than USB 3.0 when connected to a UASP-enabled host controller.

The U357-025-SEC accepts SATA III, II and I drives and is backward-compatible with previous USB generations. No software, drivers or external power supply is required. Compatible with any USB-enabled operating system.

### Features

#### Quickly Connects a SATA Drive to Your Computer's USB 3.0 Port

- Recommended for portable storage or backing up sensitive data

### Highlights

- Keypad lock provides password security for important files
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Works up to 70% faster when connected to UASP host controller
- Compatible with 2.5 in. SATA HDDs and SSDs up to 2 TB
- Recommended for 256-bit AES-encrypted portable storage

### System Requirements

- 2.5 in. SATA HDD or SSD with 9.5 mm maximum height
- Device with USB port (USB 3.0 required to achieve USB 3.0 speeds)
- USB-enabled operating system
- UASP-enabled host controller required for UASP performance

### Package Includes

- U357-025-SEC USB 3.0 SuperSpeed to 2.5 in. SATA Encrypted Hard Drive Enclosure
- USB 3.0 A to Micro-B device cable, 2 ft.
- Owner's manual



- Supports USB 3.0 data transfer rates up to 5 Gbps
- Features UASP for performance up to 70% faster when connected to UASP-enabled host controller
- Compatible with any USB-enabled operating system

#### State-of-the-Art Security Protects Your Data

- Real-time 256-bit AES encryption protects data from unauthorized access
- Secure keypad lock provides password security for sensitive documents and files
- Custom password can be changed as often as you like

#### Compatible with 2.5 in. SATA Drives Up to 2 TB

- Accepts SATA III, II and I drives
- Backward compatible with previous USB generations
- Works with both SATA HDDs and SSDs

#### Built for Portable Use

- Plug and play—no software, drivers or external power supply needed
- Portable tool-free design for quick on-the-move external storage
- SATA drive slides easily into convenient tray
- Protective cover keeps dust and dirt away from sensitive SATA drives
- USB 3.0 Micro-B device cable included

## Specifications

OVERVIEW	
UPC Code	037332200907
Drives Supported	2.5" HDD and SSD
INPUT	
Bus Powered	Yes
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Green (Read, Write, Power); Orange (PIN setting); Red (Lock); Blue (Unlock)
PHYSICAL	
Color	Black
Material of Construction	ABS
Shipping Dimensions (hwd / cm)	4.57 x 12.70 x 18.03
Shipping Dimensions (hwd / in.)	1.80 x 5.00 x 7.10
Shipping Weight (kg)	0.23



Shipping Weight (lbs.)	0.50
Unit Dimensions (hwd / cm)	1.8 x 12 x 7.8
Unit Dimensions (hwd / in.)	0.71 x 4.7 x 3.1
Unit Packaging Type	Box
Unit Weight (kg)	0.09
Unit Weight (lbs.)	0.2
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	50 to 122 F (10 to 50 C)
Storage Temperature Range	32 to 149 F (0 to 65 C)
Relative Humidity	10% to 80% RH, Non-Condensing
BTUs	17.1 BTU/Hr
Power Consumption (Watts)	5
<b>CONNECTIONS</b>	
Ports	1
Side A - Connector 1	USB 3.0 A (MALE)
Side B - Connector 1	22 PIN SATA + POWER (FEMALE)
Connector Plating	Nickel
<b>FEATURES &amp; SPECIFICATIONS</b>	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
UASP Support	Yes
Technology	USB 3.0 (SuperSpeed); SATA/eSATA; USB
<b>CERTIFICATIONS</b>	
Certifications	Tested to CE, FCC, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>