



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Tripp Lite Waber Industrial Power Strip, 6-Outlet, 15-ft. Cord, Locking Switch Cover

MODEL NUMBER: **UL24CB-15**



### Highlights

- 6 outlets
- 15 ft. cord
- 12.5" length
- All metal housing
- Lighted master switch

### Package Includes

- UL24CB-15 Power Strip
- Warranty information
- Instruction manual

### Description

The Waber-by-Tripp Lite UL24CB-15 Power Strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles with 1.625 inch center-to-center spacing, 15 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes UL24CB-15 ideal for distributing alternate waveform UPS or generator power. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15 amp resettable circuit breaker and attractive blue/gray color scheme.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles with 1.625 inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity with circuit breaker
- 15 foot AC line cord

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332115546 |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| OUTPUT   |  |
|--|--|
| Frequency Compatibility                              | 50 / 60 Hz   |
| Output (Watts)                                       | 1800   |
| Output Receptacles                                   | (6) 5-15R  |
| Circuit Breaker (amps)                               | 15   |
| Transformer Accommodation                            | (2) Yes  |
| Outlet Spacing                                       | 1.625 in.  |
| Outlet Orientation                                   | Single row of 6  |
| Right-Angle Outlets                                  | No   |
| INPUT  |  |
| Nominal Input Voltage(s) Supported                   | 120V AC  |
| Recommended Electrical Service                       | 15A 120V   |
| Input Cord Gauge Type                                | 14 gauge; SJT  |
| Voltage Compatibility (VAC)                          | 120  |
| Input Plug Type                                      | NEMA 5-15P   |
| Input Cord Length (ft.)                              | 15   |
| Input Cord Length (m)                                | 4.57   |
| Integrated Cord Clip                                 | No   |
| USER INTERFACE, ALERTS & CONTROLS                    |  |
| Switches   | Lighted 2 position switch controls power to all outlets      |
| Locking Switch Cover                                 | Transparent on/off switch cover prevents accidental turn-off |
| PHYSICAL   |  |
| Anti-Microbial Protective Coating                    | No   |
| Color  | Gray   |
| Color (AC Line Cord)                                 | Black  |
| Integrated Keyhole Mounting Slots                    | Yes (Includes flanges)                                       |
| Keyhole Slot Mounting Measurement (Center to Center) | 261.92mm   |
| Material of Construction                             | Metal  |
| Outlets Measurement (Center to Center)               | 41.3mm   |
| Receptacle Color                                     | Black  |
| Shipping Dimensions (hwd / cm)                       | 35.81 x 5.72 x 15.24   |
| Shipping Dimensions (hwd / in.)                      | 14.10 x 2.25 x 6.00  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                           |
|-------------------------------------|---------------------------|
| Shipping Weight (kg)                | 1.45                      |
| Shipping Weight (lbs.)              | 3.20                      |
| Unit Dimensions (hwd / cm)          | 31.75 x 6.35 x 3.8        |
| Unit Dimensions (hwd / in.)         | 12.5 x 2.5 x 1.5          |
| <b>CERTIFICATIONS</b>               |                           |
| UL1363 (Power Tap)                  | UL1363                    |
| Canada                              | cUL                       |
| <b>WARRANTY</b>                     |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>