ISM 868 MHz PCB Substrate Antenna (EVB+AA067)

Engineering Specification

1. Explanation of Product Number

H 2 B 1 S G 1 A 1 S 0 4 0 0



2. Features

- *Stable and reliable in performances
- *Low temperature coefficient of frequency
- *Low profile, compact size
- *RoHS 2.0 compliance
- *SMT processes compatible

(EVB+AA067) Engineering Specification

3. Applications

- *ISM Band system.
- *RFID system

4. Description

Unictron's chip antenna series are specially designed for ISM Band applications. Based on Unictron's proprietary design and processes, this chip antenna has excellent stability and sensitivity to consistently provide high signal acception efficiency.



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Α

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE : ISM 868 MHz PCB Substrate Antenna DOCUMENT H2B1SG1A1S0400 REV.

PAGE 1 OF 10

NO.

5. Electrical Specifications (80x40(mm) ground plane)


5-1. Electrical Table:

Characteristics		Specifications	Unit
Outline Dimensions		10x3.2x0.5	mm
Ground Plane		80x40	mm
Working Frequency		863~870	MHz
VSWR (@ center frequency)*		2 Max.	
Characteristic Impedance		50	Ω
Polarization		Linear Polarization	
Peak Gain	(@015MUz)	0.5(typical**)	dBi
Efficiency	(@915MHz)	60(typical**)	%

^{*}Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board..


5-2. Return Loss & VSWR

Return Loss (S₁₁)



(EVB+AA067) Engineering Specification

VSWR (S₁₁)



2018-08-16

Document

Α

Unictron Technologies Corp.

詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE : ISM 868 MHz PCB Substrate Antenna DOCUMENT H2B1SG1A1S0400 REV.

NO.

^{**}A typical value is for reference only, not guaranteed.


Antenna Dimensions & Test Board (unit: mm) 6-1. Antenna Dimensions A10±0.2 Feed Side **Top View Front View Right View Left View** 1.All materials are RoHS 2.0 compliant. **Bottom View** 2." A~©" Critical Dimensions. 3."()" Reference Dimensions. **PIN Definitions** PIN1 | 868 PIN₂ PIN₂ PIN₁ **Top View Bottom View** PIN 1 Unictron hnologies Corp. **Soldering PAD** Signal Tuning / Ground 2018-08-16 THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES 詠業科技股份有限公司 CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR **Unictron Technologies Corporation** SALE OF APPARATUS OR DEVICES WITHOUT Website:www.unictron.com PERMISSION

Prepared by : Mina	Designed by : Ken	Checked by : Mike	Approved by : Herbert	UNIT : mm
TITLE: ISM 868 MHz PC	B Substrate Antenna	DOCUMENT	H2B1SG1A1S0400	REV.

(EVB+AA067) Engineering Specification


PAGE 3 **OF** 10


NO.





7. Radiation Pattern (80x40(mm) ground plane)

7-1. 3D Gain Pattern (Radiation Pattern at 868 MHz)











詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE: ISM 868 MHz PCB Substrate Antenna (EVB+AA067) Engineering Specification

DOCUMENT NO.

H2B1SG1A1S0400


REV.

7-2. 3D Efficiency Table

Frequency(MHz)	856	857	858	859	860	861	862	863	864	865	866	867
Efficiency (dB)	-7.46	-7.01	-6.54	-6.07	-5.59	-5.11	-4.64	-4.17	-3.71	-3.28	-2.87	-2.51
Efficiency (%)	17.95	19.92	22.19	24.73	27.61	30.81	34.35	38.28	42.59	47.04	51.66	56.08
Gain (dBi)	-4.84	-4.39	-3.93	-3.43	-2.96	-2.44	-1.96	-1.47	-0.99	-0.56	-0.12	0.23

Frequency(MHz)	869	870	871	872	873	874	875	876	877	878	879	880
Efficiency (dB)	-2.00	-1.89	-1.86	-1.92	-2.07	-2.29	-2.58	-2.92	-3.31	-3.72	-4.14	-4.57
Efficiency (%)	63.04	64.64	65.20	64.23	62.08	58.99	55.19	51.00	46.68	42.47	38.55	34.93
Gain (dBi)	0.78	0.91	0.96	0.90	0.75	0.53	0.23	-0.11	-0.49	-0.90	-1.34	-1.78

7-3. 3D Efficiency vs. Frequency



Unictron Technologies Corp.

2018-08-16

Α

詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


Checked by : Mike Prepared by : Mina Designed by: Ken Approved by : Herbert UNIT: mm TITLE:ISM 868 MHz PCB Substrate Antenna **DOCUMENT** REV. H2B1SG1A1S0400 (EVB+AA067) Engineering Specification NO.

8. Layout Guide:

a. Solder Land Pattern:


Land pattern for soldering (black marking areas) is as shown below. Matching circuit is needed for good performance, when customer's device is different.





b. Matching circuit:

(Center frequency is about 915 MHz @ 80 x 40 mm² Evaluation Board)



8	System Matching Circuit Component					
Location	Description	Vendor	Tolerance			
1	N/A*	-	-			
2	0Ω*	(0402)	-			
3	5.0pF*	Murata (0402)	±0.05 pF			
4	12pF*	Murata (0402)	±5 %			

^{*}Typical reference values which may need to be changed when circuit boards or part vendors are different.

Unictron
Technologies Corp.

2018-08-16

Document

Unictron
Technologies Corp.

詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE: ISM 868 MHz PCB Substrate Antenna (EVB+AA067) Engineering Specification (EVB+AA067) Engineering Speci

9. Soldering Conditions:

a. Typical Soldering Profile for Lead-free Process



10. Reminders for users of Unictron's chip antennas

- a. Since Unictron's chip antennas are made of ceramic materials which show different rigidity than circuit board materials, bending of circuit board at the locations where chip antennas are mounted may cause the cracking of solder joints or antenna itself.
- b. Any connecting strip which will be cut off at PCB assembly process shall be located away from the installation site of chip antenna. Punching of the connecting strip may cause severe bending of the circuit board and cracking of solder joint or chip antenna itself may occur.
- c. Be cautious when ultrasonic welding process needs to be used near the locality of corp. where chip antennas are installed. Strong ultrasonic vibration may cause the cracking of chip antenna solder joints.



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE : ISM 868 MHz PCB Substrate Antenna (EVB+AA067) Engineering Specification

DOCUMENT NO.

H2B1SG1A1S0400


A

11. Packing:

(1) Quantity/Reel: 6000pcs/Reel

(2) Plastic tape:

a. Tape Drawing



b. Tape Dimensions (unit: mm)

Feature	Specifications	Tolerances
W	24.00	±0.30
Р	8.00	±0.10
E	1.75	±0.10
F	11.50	±0.10
P2	2.00	±0.10
D	1.50	+0.10 0.00
D1	1.50	±0.10
Po	4.00	±0.10
10Po	40.00	±0.20

12. Operating & Storage Conditions

12-1. Operating

(1) Maximum Input Power: 2 W

(2) Operating Temperature: -40°C to 85°C

(3) Relative Humidity: 10% to 70%

12-2. Storage (sealed)

(1) Storage Temperature: -5°C to 40°C

(2) Relative Humidity: 20% to 70%

(3) Shelf Life: 1 year

12-3. Storage (unsealed)

Meet the criteria of <u>J-STD-033 MSL2a</u>

12-4. Storage (After mounted on customer's PCB with SMT process) hictron

(2) Relative Humidity: 10% to 70%

Technologies Corp.

2018-08-16

Document Control Cont



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE : ISM 868 MHz PCB Substrate Antenna (EVB+AA067) Engineering Specification

DOCUMENT NO.

H2B1SG1A1S0400

A

13. Notice

(1) Installation Guide:

Please refer to Unictron's application note "General guidelines for the installation of Unictron's chip antennas" for further information.

(2) All specifications are subject to change without notice.

Unictron Technologies Corp.

2018-08-16

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Mina Designed by : Ken Checked by : Mike Approved by : Herbert UNIT : mm

TITLE: ISM 868 MHz PCB Substrate Antenna (EVB+AA067) Engineering Specification

DOCUMENT NO.

H2B1SG1A1S0400
A