






## Schottky Barrier Rectifier

 Reverse Voltage 35 to 60V  
 Forward Current 10A

**TO-220AC (MBR10xx)**

**ITO-220AC (MBRF10xx)**

**Mounting Pad Layout TO-263AB**

**TO-263AB (MBRB10xx)**


## Features

- Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- Guardring for overvoltage protection
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- High temperature soldering guaranteed:  
250°C/10 seconds, 0.25" (6.35mm) from case

## Mechanical Data

**Case:** JEDEC TO-220AC, ITO-220AC & TO-263AB molded plastic body

**Terminals:** Plated leads, solderable per MIL-STD-750, Method 2026

**Polarity:** As marked

**Mounting Position:** Any

**Mounting Torque:** 10 in-lbs maximum

**Weight:** 0.08 ounce, 2.24 grams

# MBR10xx, MBRF10xx & MBRB10xx Series



Vishay Semiconductors  
formerly General Semiconductor

## Maximum Ratings (T<sub>c</sub> = 25°C unless otherwise noted)

Parameter	Symbol	MBR1035	MBR1045	MBR1050	MBR1060	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	35	45	50	60	V
Working peak reverse voltage	V <sub>RWM</sub>	35	45	50	60	V
Maximum DC blocking voltage	V <sub>DC</sub>	35	45	50	60	V
Maximum average forward rectified current (See Fig. 1)	I <sub>F(AV)</sub>		10			A
Peak repetitive forward current at T <sub>c</sub> = 135°C (sq. wave, 20 KHz)	I <sub>FRM</sub>		20			A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) per leg	I <sub>FSM</sub>		150			A
Peak repetitive reverse current per leg at t <sub>p</sub> = 2.0μs, 1KHz	I <sub>RRM</sub>	1.0		0.5		A
Voltage rate of change (rated V <sub>R</sub> )	dV/dt		10,000			V/μs
Operating junction temperature range	T <sub>J</sub>		-65 to +150			°C
Storage temperature range	T <sub>STG</sub>		-65 to +175			°C
RMS Isolation voltage (MBRF type only) from terminals to heatsink with t = 1.0 second, RH ≤ 30%	V <sub>ISOL</sub>	4500 <sup>(1)</sup> 3500 <sup>(2)</sup> 1500 <sup>(3)</sup>				V

## Electrical Characteristics (T<sub>c</sub> = 25°C unless otherwise noted)

Parameter	Symbol	MBR1035	MBR1045	MBR1050	MBR1060	Unit
Maximum instantaneous forward voltage per leg <sup>(4)</sup> at I <sub>F</sub> = 10A, T <sub>c</sub> = 25°C at I <sub>F</sub> = 10A, T <sub>c</sub> = 125°C at I <sub>F</sub> = 20A, T <sub>c</sub> = 25°C at I <sub>F</sub> = 20A, T <sub>c</sub> = 125°C	V <sub>F</sub>	— 0.57 0.84 0.72		0.80 0.70 0.95 0.85		V
Maximum instantaneous reverse current at rated DC blocking voltage <sup>(4)</sup>	I <sub>R</sub>		0.10 15			mA

## Thermal Characteristics (T<sub>c</sub> = 25°C unless otherwise noted)

Parameter	Symbol	MBR	MBRF	MBRB	Unit
Maximum thermal resistance, junction to case	R <sub>θJC</sub>	2.0	4.0	2.0	°C/W

### Notes:

- (1) Clip mounting (on case), where lead does not overlap heatsink with 0.110" offset
- (2) Clip mounting (on case), where leads do overlap heatsink
- (3) Screw mounting with 4-40 screw, where washer diameter is ≤ 4.9 mm (0.19")
- (4) Pulse test: 300μs pulse width, 1% duty cycle


## Ordering Information

Product	Case	Package Code	Package Option
MBR1035 - MBR1060	TO-220AC	45	Anti-Static tube, 50/tube, 2K/carton
MBRF1035 - MBRF1060	ITO-220AC	45	Anti-Static tube, 50/tube, 2K/carton
MBRB1035 - MBRB1060	TO-263AB	31 45 81	13" reel, 800/reel, 4.8K/carton Anti-Static tube, 50/tube, 2K/carton Anti-Static 13" reel, 800/reel, 4.8K/carton


## Ratings and Characteristic Curves

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig. 1 - Forward Current Derating Curve**




**Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current**




**Fig. 3 - Typical Instantaneous Forward Characteristics**




**Fig. 4 - Typical Reverse Characteristics**



**Fig. 5 - Typical Junction Capacitance**



**Fig. 6 - Typical Transient Thermal Impedance**





## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.