

**HDC insert
FPL 4G2.5C/Q8MW/3**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

General ordering data

Type	FPL 4G2.5C/Q8MW/3
Order No.	8000011748
Version	FieldPower®, Cable, Metal housing, No. of wires: 4, Ölflex Classic 110 CY 4G2.5 or similar, Cross-section: 2.5 mm ² , 3 m
GTIN (EAN)	4050118190427
Qty.	1 pc(s).

Data sheet

HDC insert
FPL 4G2.5C/Q8MW/3

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 915 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

General data

Cable length, string 1	3 m	Cross-section	2.5 mm ²
Line type	Ölflex Classic 110 CY 4G2.5 or similar	No. of wires	4

Technical data

Rated current	16 A	Rated voltage	500 V
Rated voltage U0	300 V		

Classifications

ETIM 5.0	EC001576	ETIM 6.0	EC001578
eClass 6.2	27-06-04-90	eClass 7.1	27-06-04-90
eClass 8.1	27-06-04-90	eClass 9.0	27-06-20-11
eClass 9.1	27-06-90-90		

Approvals

Approvals



Data sheet

**HDC insert
FPL 4G2.5C/Q8MW/3**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Drawings

Pin assignments

	Pin	Conductor	Assignment
8 - nc	1	1	U
	2	-	-
5 - nc	3	3	W
	4	-	-
PE	5	-	-
	6	-	-
3 - W	7	2	V
	8	-	-
2 - nc	PE	gr./yell.	PE

