

RS 70
ZW 25 RS OR**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

The RS 70 profile is supplied in fixed lengths. The desired length is obtained by connecting the individual pieces together. The PCB is pushed into the side of the profile. End cover plates close off the sides of the profile.. Elements for terminal rails and direct mounting are available here. The clip-on feet are permanently attached to the profile. Marking options are integrated into the side pieces.

General ordering data

| | |
|------------|---|
| Type | ZW 25 RS OR |
| Order No. | 0126160000 |
| Version | Electronics housings, RS 70 Orange, Intermediate part, Width: 25 mm |
| GTIN (EAN) | 4008190153809 |
| Qty. | 20 pc(s). |

**RS 70
ZW 25 RS OR**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|--------|---------|------------|-------|
| Length | 70 mm | Width | 25 mm |
| Height | 33.5 mm | Net weight | 6.3 g |

System characteristics

| | | | |
|-------------------|-------------------|-----------------------------|------|
| Version | Intermediate part | Number of PCBs per module | 1 |
| PCB thickness | 1.6 mm | Tolerance for the PCB shape | ±0.2 |
| Cross-connection | No | Contact to terminal rail | No |
| Protection degree | IP 20 | Encapsulation option | No |

Material data

| | | | |
|---------------------------|--------|---------------------------------------|-------|
| UL 94 flammability rating | V-2 | Insulating material | PA 66 |
| Colour | Orange | Max. relative humidity during storage | 93 % |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001284 | UNSPSC | 30-21-18-01 |
| eClass 6.2 | 27-14-92-14 | eClass 7.1 | 27-14-92-14 |

Approvals

| | |
|-----------|---------|
| Approvals | |
| ROHS | Conform |