



RECOMMENDED LAYOUT

**TECHNICAL CHARACTERISTICS**

**SPECIFICATION**

- >**Contact Rating:**
  - Switching: 150mA, 24VDC
  - Non-Switching: 400mA, 24VDC
- >**Contact Resistance:**
  - Initial: 80mOHM max.
  - After Life Test: 200mOHM max.
- >**Insulation Resistance:** min. 100MOHM at 250VDC
- >**Dielectric Strength:** 250VAC for 1 minute
- >**Operating Force:** 700g max.
- >**Life cycle:** 10.000 steps
- >**Position:** 8
- >**Actuator:** Arrow type

**MATERIAL**

- >**Cover:** PA66 UL 94V-0, color light grey
- >**Base:** PA66 UL 94V-0, color black
- >**Actuator:** POM UL HB
- >**Contact:** Gold Plated
- >**Terminal:** Gold Plated

**SOLDERING INFORMATION**

- >**Terminal in THT version**
- >**Wave soldering 260°C for 10 sec. max**
- >**Hand soldering at 350°C for 3 sec. max**

**WASHABLE DEFINITION**

Please do not submerge washable products into water or cleaning agents or put them in locations exposed to water or liquids completely. When cleaning by hand (brushing), please do not use excessive force on our switch to avoid malfunction afterwards, because you could deform function relevant areas or you could damage sealing functions. Do not clean washable series immediately after soldering. The cleaning agent may be absorbed into the switch through respiration while the switch cools.

**ENVIRONMENTAL**

- >**Storage condition:** -40°C ~ +85°C
- >**Operation condition:** -40°C ~ +85°C
- >**Compliance:** Lead Free, ROHS, Reach

**PACKAGING INFORMATION**

Part number	Color of Actuator	Position	Code
428 527 320 908	dark grey	08	Real Code
428 527 320 909	ivory	08	Complement Code

Real Code					
08 Position	C 1 2 4 8				
0	•	•	•	•	•
1	•	•	•	•	•
2	•	•	•	•	•
3	•	•	•	•	•
4	•	•	•	•	•
5	•	•	•	•	•
6	•	•	•	•	•
7	•	•	•	•	•

Complement Code					
08 Position	C 1 2 4 8				
0	•	•	•	•	•
1	•	•	•	•	•
2	•	•	•	•	•
3	•	•	•	•	•
4	•	•	•	•	•
5	•	•	•	•	•
6	•	•	•	•	•
7	•	•	•	•	•

Scale - 3:1

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

			<b>GENERAL TOLERANCE</b> .x = +/- 0,2 .xx = +/- 0,15		Basic material	
			Date 13-03-25	Name Jelisarow		<b>DESCRIPTION</b> WS-ROTV 10x10 Rotary Switch, 08 position, THT version
			Checked 13-03-25	Hsu		
b	revised MatchCode	14-07-25	AL	Würth Elektronik eiCan		Scale 3:1
a	Washable Definition	14-03-05	DaF			Position
REV	FILE	DATE	BY			Drawing.- No. 42852732090x
						SIZE A4
						System :Solid Edge ST4